



Sparkle Power Inc.

A Leading Power Supply Manufacturer

Web site: www.sparklepower.com

SPR2C620(RoHS Compliant)

620 Watts 1+1, 2U Hot-Swap Redundant Switching Power Supply

Features

- Complied with ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by UL/CUL60950-1, CCC, TUV EN60950 -1, CB report ,FCC,EMC

Input Characteristics

Input Range: 90 ~ 264Vac (RMS), Full Range Input

Frequency: 47 ~ 63Hz

Input Current: Max 8.5A (RMS) @ 110Vac, 4.0A (RMS) @ 220Vac

Inrush Current:80A Max@ 100~240Vac Cold start

Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0.5A	12A	24A	± 5%	50mV P-P
+5V	0.5A	12.5A	25A	± 5%	50mV P-P
+12V1	0.5A	8A	16A	± 5%	120mV P-P
+12V2	0.5A	8A	16A	± 5%	120mV P-P
+12V3	1.0A	8A	16A	± 5%	120mV P-P
-12V	0.0A	0.25A	0.5A	± 10%	120mV P-P
-5V	0.0A	0.1A	0.2A	± 10%	120mV P-P
+5Vsb	0.0A	1.0A	2.0A	± 5%	50mV P-P

*+3.3V and +5V total output not exceed 150W

*Maximum combined current for the 12V outputs shall be 42A.

* Total output for this subject power supply is620W



Specification

- **Temperature Range:** Operating: 0°C ~ +50°C on full load; storage & shipping: -40°C ~ +70°C
- **Humidity:** 5-85% on operating,5-95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 3 second
- **Efficiency:** Min **65%** @ 100% Load & 72% @ 50% load
- **Rise time:** Less than 70msec
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time5 ~ 400ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 300mm*101mm*84.4mm /11.8 x 4x3.3 inch

Sparkle Power Inc. Main Office

1000 Rock Avenue
San Jose, CA 95131
TEL: 408-519-8888
FAX: 408-519-9999
E-MAIL: info@sparklepower.com

Sparkle Power Inc. Los Angeles Office

17071 Green Drive
City of Industry, CA 91745
TEL: 626-839-7180
FAX: 626-839-3395