


CUT-OUT

Nut Torque: 5 ~ 14Nm
 Operating Pressure: 400gf ±150gf
 Operating Stroke: 1.8mm±0.3
 Protection Grade: IP65
 Function: (ON)-OFF
 Base: PA66
 Shell: Brass, Ni Plating
 Button: SUS
 Lamp Type: LED
 Lamp Life: 50000H
 Rating: 0.2A 250V AC/0.5A 12V DC
 Contact Resistance: 50mΩ Max
 Insulation Resistance: 100MΩ Min
 Dielectric Strength: 1500V AC 1 minute
 Electrical life: 50,000 cycles
 Mechanical life: 200,000 cycles
 Operating Temperature: -20°C~80°C
 Relative Air Humidity: 45%~85%
 Safety Approval:



公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				版本 VERSION	比例尺 SCALE	日期 DATE	PBM-12M12-FT-G1-R6-B8S	PBM-12M12-FT-G1-R6-B8S_A0
				A0	1:1	2021.04.07		