



SHEET 1 OF 1







▲SCHEMATIC









NOTES
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=± 0.4
   X.XX=± 0.25
3. TERMINAL NUMBERS FOR REF. ONLY.
▲4. OPERATING FORCE: 130± 50gf
5. OPERATING LIFE: 1,000,000 CYCLES
6. TRAVEL: 0.5± 0.15mm
7. CONTACT RATING: 12VDC @ 50mA
8. CONTACT RESISTANCE: 100m Ω MAX
9. INSULATION RESISTANCE: 100M Ω MIN @ 100VDC.
▲10. CONTACT MATERIAL: SILVER
11. OPERATING TEMPERATURE: -40˚C TO 85˚C
12. PACKAGING: TUBE 52 PCS. PER TUBE
13. ▲DENOTES CRITICAL PARAMETER
14. 2002/95/EC (ROHS) COMPLIANT

REV	PCR NO	DESCRIPTION	DATE	BY
B	21552	CORRECT NOTED TOLERANCE	8/19/14	EBP
A	21167	New Release	6/18/13	rc

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E•SWITCH®

TITLE TL6110BF130QP

SCALE	DATE	DR	DWG	REV
	6/18/2013	rc	T351002	B