

# LA1DY20

Auxiliary contact block, TeSys D, 2NO (sealed), front mounting, screw clamp terminals

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 77.00 USD



## Main

Range	TeSys
Product name	TeSys D
Product or Component Type	Auxiliary contact block
Device short name	LA1
Range compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F
Mounting Location	Front
Pole contact composition	2 earth screen continuity poles 2 NO (sealed)
Contacts operation	Instantaneous
[Ue] rated operational voltage	125 V AC protected contact 30 V DC protected contact
[Ie] rated operational current	0.1 A125 V AC-12 0.1 A30 V DC-12
[Ui] rated insulation voltage	125 V IEC 60947-5-1
[Ith] conventional free air thermal current	0.1 A 104 °F (40 °C)
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Product Certifications	IECEE CB Scheme UL CSA CCC EAC UKCA

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Complementary

Mechanical durability	5 Mcycles
Minimum switching current	1 mA
Minimum switching voltage	5 V
Insulation resistance	> 10 MOhm
Connections - terminals	screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible without cable end screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible without cable end screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )rigid screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )rigid
Tightening torque	15.05 lbf.in (1.7 N.m) flat Ø 6 mm 15.05 lbf.in (1.7 N.m) Philips No 2
Height	1.89 in (48 mm)
Width	1.73 in (44 mm)
Depth	1.54 in (39 mm)
Product Weight	0.09 lb(US) (0.04 kg)
Quantity per Set	Set of 2

## Environment

Environmental characteristic	Harsh environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)

## Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	03389110236514
Nbr. of units in pkg.	1
Package weight(Lbs)	2.22 oz (63 g)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	1.89 in (4.8 cm)
Package 1 Length	2.05 in (5.2 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	22.33 oz (633 g)
Package 2 Height	1.97 in (5 cm)
Package 2 width	3.35 in (8.5 cm)
Package 2 Length	10.24 in (26 cm)
Unit Type of Package 3	S02
Number of Units in Package 3	80
Package 3 Weight	12.19 lb(US) (5.528 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	11.81 in (30 cm)

Package 3 Length	15.75 in (40 cm)
------------------	------------------

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------