

HM1N60


主要参数 MAIN CHARACTERISTICS


I_D	0.5 A	TO-92
	1.0 A	IPAK/DPKA
V_{DSS}	600 V	
Rdson（Vgs=10V）	15 Ω	
Qg	6.1 nC	

封装 Package









用途

- 高频开关电源
- 电子镇流器

APPLICATIONS

- High efficiency switch mode power supplies
- Electronic lamp ballasts based on half bridge

产品特性

- 低栅极电荷
- 低 C_{rss} (典型值 3.7pF)
- 开关速度快
- 产品全部经过雪崩测试
- 高抗 dv/dt 能力
- RoHS 产品

FEATURES

- Low gate charge
- Low C_{rss} (typical 3.7pF)
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability
- RoHS product

订货信息 ORDER MESSAGE

订 货 型 号 Order codes	印 记 Marking	封 装 Package	无卤素 Halogen Free	包 装 Packaging	器件重量 Device Weight
HM1N60	HM1N60	TO-92	否 NO	编带 Brede	0.216 g(typ)
HM1N60I	HM1N60I	IPAK	否 NO	条管 Tube	0.350 g(typ)
HM1N60K	HM1N60K	DPAK	否 NO	条管 Tube	0.300 g(typ)

绝对最大额定值 ABSOLUTE RATINGS (Tc=25℃)

项 目 Parameter	符 号 Symbol	数 值 Value		单 位 Unit
		HM1N60	HM1N60I/K	
最高漏极－源极直流电压 Drain-Source Voltage	V_{DSS}	600	600	V
连续漏极电流 Drain Current -continuous	I_D T=25℃	0.5	1.0	A
	T=100℃	0.31	0.62	A
最大脉冲漏极电流（注 1） Drain Current - pulse （note 1）	I_{DM}	2.0	4.0	A
最高栅源电压 Gate-Source Voltage	V_{GSS}	±30		V
单脉冲雪崩能量（注 2） Single Pulsed Avalanche Energy （note 2）	E_{AS}	47		mJ
雪崩电流（注 1） Avalanche Current（note 1）	I_{AR}	1.0		A
重复雪崩能量（注 1） Repetitive Avalanche Current （note 1）	E_{AR}	3.0		mJ
二极管反向恢复最大电压变化速率（注 3） Peak Diode Recovery dv/dt （note 3）	dv/dt	4.2	4.2	V/ns
耗散功率 Power Dissipation	P_D T_C=25℃	3.0	30	W
	-Derate above 25℃	0.025	0.24	W/℃
最高结温及存储温度 Operating and Storage Temperature Range	T_J，T_{STG}	-55～+150		℃
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	T_L	300		℃

电特性 ELECTRICAL CHARACTERISTICS

项　　目 Parameter	符　号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单　位 Units
关态特性 Off –Characteristics						
漏－源击穿电压 Drain-Source Voltage	BV_{DSS}	I_D=250μA, V_{GS}=0V	600	-	-	V
击穿电压温度特性 Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_J$	I_D=1mA, referenced to 25℃	-	0.60	-	V/℃
零栅压下漏极漏电流 Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=600V,V_{GS}=0V, T_C=25℃	-	-	10	μA
		V_{DS}=480V, T_C=125℃	-	-	100	μA
正向栅极体漏电流 Gate-body leakage current, forward	I_{GSSF}	V_{DS}=0V, V_{GS} =30V	-	-	100	nA
反向栅极体漏电流 Gate-body leakage current, reverse	I_{GSSR}	V_{DS}=0V, V_{GS} =-30V	-	-	-100	nA
通态特性 On-Characteristics						
阈值电压 Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS} , I_D=250μA	2.0	-	4.0	V
静态导通电阻 Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS} =10V , I_D=0.5A	-	11	15	Ω
正向跨导 Forward Transconductance	g_{fs}	V_{DS} = 40V , I_D=0.5（note 4）	-	0.8	-	S
动态特性 Dynamic Characteristics						
输入电容 Input capacitance	C_{iss}	V_{DS}=25V, V_{GS} =0V, f=1.0MHz	-	178	221	pF
输出电容 Output capacitance	C_{oss}		-	19	27	pF
反向传输电容 Reverse transfer capacitance	C_{rss}		-	3.7	4.8	pF

电特性 ELECTRICAL CHARACTERISTICS

开关特性 Switching Characteristics						
延迟时间 Turn-On delay time	$t_d(on)$	V_{DD}=300V,I_D=1.0A,R_G=25Ω （note 4，5）	-	15	45	ns
上升时间 Turn-On rise time	t_r		-	46	105	ns
延迟时间 Turn-Off delay time	$t_d(off)$		-	26	62	ns
下降时间 Turn-Off Fall time	t_f		-	37	82	ns
栅极电荷总量 Total Gate Charge	Q_g	V_{DS} =480V , I_D=1.0A V_{GS} =10V （note 4，5）	-	6.1	7.2	nC
栅－源电荷 Gate-Source charge	Q_{gs}		-	1.0	-	nC
栅－漏电荷 Gate-Drain charge	Q_{gd}		-	3.0	-	nC
漏－源二极管特性及最大额定值 **Drain-Source Diode Characteristics and Maximum Ratings**						
正向最大连续电流 Maximum Continuous Drain -Source Diode Forward Current	I_S		-	-	1.0	A
正向最大脉冲电流 Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}		-	-	4.0	A
正向压降 Drain-Source Diode Forward Voltage	V_{SD}	V_{GS}=0V, I_S=1.0A	-	-	1.0	V
反向恢复时间 Reverse recovery time	t_{rr}	V_{GS}=0V, I_S=1.0A dI_F/dt=100A/μs (note 4)	-	185	-	ns
反向恢复电荷 Reverse recovery charge	Q_{rr}		-	0.51	-	μC

热特性 THERMAL CHARACTERISTIC

项 目 Parameter	符 号 Symbol	最大 Max		单 位 Unit
		HM1N60	HM1N60I/K	
结到管壳的热阻 Thermal Resistance, Junction to Case	$R_{th(j-c)}$	—	4.75	℃/W
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{th(j-A)}$	120	105	℃/W

注释：

1：脉冲宽度由最高结温限制

2：L=59mH, I_{AS}=1.0A, V_{DD}=50V, R_G=25 Ω,起始结温 T_J=25℃

3：I_{SD} ≤1.0A,di/dt ≤200A/μs,VDD≤BV_{DSS},起始结温 T_J=25℃

4：脉冲测试：脉冲宽度≤300μs,占空比≤2%

5：基本与工作温度无关

Notes:

1 ： Pulse width limited by maximum junction temperature

2：L=59mH, I_{AS}=1.0A, V_{DD}=50V, R_G=25 Ω, Starting T_J=25℃


3 ： I_{SD} ≤1.0A,di/dt ≤200A/μs,VDD≤BV_{DSS}, Starting T_J=25℃

4：Pulse Test：Pulse Width ≤300μs,Duty Cycle≤2%


5：Essentially independent of operating temperature

特征曲线 ELECTRICAL CHARACTERISTICS (curves)


On-Region Characteristics




Transfer Characteristics




On-Resistance Variation vs. Drain Current and Gate Voltage




Body Diode Forward Voltage Variation vs. Source Current and Temperature



Capacitance Characteristics




Gate Charge Characteristics




特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Breakdown Voltage Variation vs. Temperature




On-Resistance Variation vs. Temperature




Maximum Safe Operating Area For HM1N60



Maximum Safe Operating Area For HM1N60I/K




Maximum Drain Current vs. Case Temperature




特征曲线 ELECTRICAL CHARACTERISTICS (curves)

Transient Thermal Response Curve For HM1N60




Transient Thermal Response Curve For HM1N60I/K



外形尺寸 **PACKAGE MECHANICAL DATA**

TO-92


单位 Unit ： mm



符号 symbol	min	max
A	4.5	4.7
A1	4.5	4.7
A2	3.5	3.7
c	TYP 0.45	
F1/F2	2.2	2.8
W1	17.5	18.5
W2	5.5	6.5
H1	22.0	27.0
H2	18.0	20.0
H3	15.0	17.0
H4	8.5	9.5
P1	12.5	12.9
P2	6.0	6.7
P3	12.5	12.9
T	0.40	0.45
ϕD	3.8	4.2
△H	0	1.0

外形尺寸 **PACKAGE MECHANICAL DATA**


IPAK **Gh** **单位 Unit：mm**



符号 symbol	MIN	MAX
A	2.2	2.4
b	0.7	0.9
c	0.45	0.55
D	6.0	6.3
D1	0.8	1.2
E	6.5	6.8
E1	5.2	5.5
e	2.28TYP	
F	0.45	0.55
L	6.85	7.15
L2	1.8	2.2
Q1	0.8	1.2

外形尺寸 PACKAGE MECHANICAL DATA


DPAK **Gh** **单位 Unit：mm**



符号 symbol	MIN	MAX
A	2.2	2.4
A1	0.0	0.2
b	0.7	0.9
c	0.45	0.55
D	6.0	6.3
D1	0.8	1.2
E	6.5	6.8
E1	5.2	5.5
e	2.28TYP	
F	0.45	0.55
H	9.65	10.45
L	1.0	1.3
L2	0.7	1.3

外形尺寸 **PACKAGE MECHANICAL DATA**


IPAK **Gf** **单位 Unit：mm**




符号 symbol	MIN	MAX
A	2.20	2.40
b	0.60	0.74
c	0.45	0.55
D	5.95	6.25
D1	0.95	1.25
E	6.45	6.75
E1	5.2	5.4
e	2.24	2.34
F	0.45	0.55
L	7.5	7.9
L2	1.0	2.0
Q1	0.95	1.15

外形尺寸 **PACKAGE MECHANICAL DATA**

DPAK **Gf** **单位 Unit：mm**





符号 symbol	MIN	MAX
A	2.20	2.40
A1	0	0.1
b	0.50	0.70
c	0.45	0.55
D	5.95	6.25
D1	0.95	1.25
E	6.45	6.75
E1	5.2	5.4
e	2.24	2.34
F	0.45	0.55
H	9.45	9.95
L	1.25	1.75
L2	0.6	0.9