SHEET 1 OF 1

▲	SWITCH FUNCTION		
	POS. 1	POS. 2	POS. 3
	ON	NONE	ON
	2-3	N/A	2-1



CIRCUIT: SPDT

NOTE:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
▲ 4. PLATING MATERIAL: GOLD
5. RATING: 0.4 VA MAX. @ 20 VAC MAX.
6. ELECTRIC LIFE: 40,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MΩ MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
9. OPERATING TEMP.: -30°C to 85°C
▲10. HARDWARE TO BE SHIPPED BULK
   T100000 - HEXNUT - QTY 2
   T100011 - LOCKWASHER - QTY 1
   T100015 - LOCKRING - QTY 1
11. ▲ DENOTES CRITICAL PARAMETER.







ISOMETRIC

REV	PCR NO	DESCRIPTION	DATE	BY
A	20272	RELEASED FOR PRODUCTION	11/09/11	BMA

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E•SWITCH®

TITLE 100SP1T5B1M1REH

SCALE	DATE	DR	DWG	REV
2:1	11/9/2011	BMA	ST103026	A