Features

- ✧ For IF SAW filter
- ✧ Single-ended operation
- ✧ Ceramic Surface Mount Package
- ✧ Small size
- ✧ No matching required for operation at 50Ω
- ✧ RoHS compliant (2002/95/EC), Pb-free


Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	114.9	115	115.1
Insertion Loss	dB	-	19.2	25
1.2 dB Bandwidth	MHz	-	9.27	-
3 dB Bandwidth	MHz	9.4	9.55	-
40 dB Bandwidth	MHz	-	10.77	10.85
Passband Variation	dB	-	0.9	1.2
Absolute Delay	usec	-	2.38	-
Ultimate Rejection(f0±10MHz)	dB	50	58	-
Material Temperature coefficient	KHz/°C	-9.43		
Substrate Material	-	128LN		
Ambient Temperature	°C	25		
DC Voltage	V	0		
Input Power	dBm	-	-	10
ESD Class	-	1A		
Package Size	SMD24.6x9.0			

Notes:

1. All specifications are based on the test circuit shown;
2. In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
4. This is the optimum impedance in order to achieve the performance show.


Matching Configuration



Source/Load Impedance=50 ohm

Notes - Component values may change depending on board layout.

Package Dimension



Pad Configuration:

Input: 10

Output: 5

Ground: All Others


Marking Configuration:

1) •: Pad Number 1 Index
2) SIPAT: Manufacturer Name
3) LBN11565: Part Number
4) XXYY: Date(Year/month)
5) ZZ: Identified Code

Package: SMD24.6x9.0 **Unit: mm**


Typical Performance

Frequency Response




Horizontal: 5MHz/Div Vertical: 10dB/Div

Passband Response




Horizontal: 5MHz/Div Vertical: 0.5dB/Div

Group Delay Variation(f0±4.5MHz)




Horizontal: 5MHz/Div Vertical: 200ns/Div

Phase Linearity(f0±4.5MHz)



Horizontal: 5MHz/Div Vertical: 10deg/Div

Smith Chart S11



Smith Chart S22

