

# SPU-1500-US



- 1500 VA/ 900W line interactive UPS
- Built-in super smart charger, shorten 50% of charging time
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- USB/RS-232 communication port
- RJ-45 surge protection
- LCD front panel interface

Line Interactive UPS

MODEL	SPU-1500-US
CAPACITY	1500 VA / 900 W
<b>INPUT</b>	
Voltage	110/120 VAC
Voltage Range	81-145 VAC
Frequency Range	60/50 Hz (auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	±10%
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz
Transfer Time	Typical 2-6 ms, 10ms max.
Waveform (Batt. Mode)	Simulated Sine Wave
<b>BATTERY</b>	
Battery Type & Number	12 V/9 Ah x 2
Typical Recharge Time	4-6 hours recover to 90% capacity
<b>PROTECTION</b>	
Full Protection	Overload, discharge, and overcharge protection
<b>INDICATORS</b>	
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Low Battery
<b>ALARM</b>	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Battery Replacement Alarm	Sounding every 2 seconds
Fault	Continuously sounding
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	495 x 150 x 250
Net Weight (kgs)	11.1
<b>ENVIRONMENT</b>	
Humidity	0-90 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 40dB
<b>MANAGEMENT</b>	
USB/RS-232 Port	Supports Windows <sup>2</sup> 2000/2003/XP/Vista/2008, Windows <sup>2</sup> 7, Linux, Unix, and MAC

\* Product specifications are subject to change without further notice

## Sparkle Power Inc.

Sparkle@SparklePower.com / www.SparklePower.com

SJ Office: 1000 Rock Ave., San Jose, CA 95131

LA Office: 17071 Green Dr., City of Industry, CA 91745

T: (408)519-8888

F: (408)519-9999

T: (626)839-7180

F: (626)839-3395