

Nut Torque: 5 ~ 14Nm

Operating Pressure: 400gf ± 200gf

Operating Stroke: 1.8mm ± 0.5

Protection Grade: IP65, IK08

Function: (ON)-OFF

Contact: Silver Alloy

Base: PA66

Shell: Brass, Ni Plating

Button: SUS

Rating (Resistive load): 3A 250V AC

Contact Resistance: 50mΩ MAX.

Insulation Resistance: 100MΩ MIN.

Dielectric Strength: 1500V AC 1 minute

Electrical life: 50,000 cycles


Mechanical life: 200,000 cycles

Operating Temperature: -20°C ~ 80°C

Relative Air Humidity: 45% ~ 85%

Safety Approval:   

SWITCHING CIRCUIT



D-SWITCH
东莞市德兹电子有限公司
D-SWITCH ELECTRONICS CO.,LTD.

公差 TOLERANCES .X± 0.5 .XX± 0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VERSION A0 比例尺 SCALE 1:1 日期 DATE 2021.04.27 品名 TITLE 图号 DRAWING NO

核准 APPROVED BY 核对 CHECKED BY 绘图 DRAWN BY 孙成 PBMM-16M11-FT-N-NN-B8L-A3 PBMM-16M11-FT-N-NN-B8L-A3_A0

版本 VER 变更说明 CHANGE DESCRIPTION

日期 DATE ECN NO.