

Clip, 5 x 20 mm, Version 3



250 VAC

**Description**

- Through hole mounting

References[General Product Information](#)**Weblinks**[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [Distributor-Stock-Check](#), [Accessories](#), [Product Change Notification \(PCN\)](#)**Technical Data**

| | |
|--------------------------|----------------------------|
| Fuse-Link | 5 x 20 mm |
| Mounting | PCB |
| Terminal | Solder THT |
| Rated Voltage | 250 VAC |
| Rated Current | 6.3 A |
| Degree of Protection | IP 00 |
| Material: Terminals | see variants |
| Unit Weight (Socket/Cap) | 0.37 g |
| Storage Conditions | 0°C to 60°C, max. 70% r.h. |
| Product Marking | none |

| | |
|------------------------------|--|
| Soldering Methods | Wave |
| Solderability | 235°C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1 |
| Resistance to Soldering Heat | 260°C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A |

Abmessungen

5.8 mm



Drilling diagram

Variants

| Clip | Terminal | Material: Terminals | Order Number |
|------|----------|---------------------|--------------|
| ● | Straight | Tin-Plated Bronze | 7181.5001 |

Packaging Unit Bulk (100 pcs.)