Data Sheet


25.0 Amp SOZA CELL AUTO DIODE

Description



SOZA CELL

Mechanical Dimensions



Dimensions in inches and (millimeters)

Features

- ✶ Low forward voltage drop
- ✶ High current capability
- ✶ High reliability
- ✶ High surge current capability

Mechanical Data

- ✶ Case: OFC Heat Sink
- ✶ Encap: Epoxy Sealed Rated UL94V-0
- ✶ Weight: 4.92 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

	SYMBOL	SCFR2502	SCFR2504	SCFR2506	UNIT
Maximum Peak Repetitive Reverse Voltage@Irrm=10uA	V_{RRM}	200	400	600	V
Maximum RMS Voltage	V_{RMS}	140	280	420	V
Maximum DC Blocking Voltage(T_A=25°C)	V_B	200	400	600	V
Maximum Average Forward Current Io@Tc=150°C 60 Hz, resistive or inductive load	$I_{(AV)}$	25			A
Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	400			A
Maximum Inst. Forward Voltage Drop, I_F at 80Amp	V_F	1.08			V
Maximum DC Reverse Current (V_B)@T_J=25°C At Rated DC Blocking Voltage (V_B)@T_J=175°C	I_R	5 250			uA uA
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-40 to +175			°C

Data Sheet

25.0 Amp SOZA CELL AUTO DIODE

RATINGS AND CHARACTERISTIC CURVES SCFR2502 ~SCFR2506

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

