



### FEATURES:

- Meets requirements of MIL-P-55149/1A.

### MATERIALS:

Binding Post Body, Nuts, Lockwasher: Gold Plated Brass  
 Insulation: Nylon MIL-P-20693  
 Flat Washer: Brass  
 Insulator: Nylon  
 Hex Nut: Steel

### RATINGS:

Voltage: Hand-held testing: 30VAC/60VDC Max.  
 Hands free testing in controlled voltage environments: 1500 VRMS  
 Operating Temperature: +80°C (+176°F) Max.  
 Current: 30 Amperes

**ORDERING INFORMATION:** Model 5018-  
 \*=Color, -0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue, -9 White  
 Ordering Example: 5018-2 Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies. Made in USA

# Pomona<sup>®</sup>

**Model 5018**  
**Hex Head Binding Post**

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02$ " (.51 mm), .xxx =  $\pm .005$ " (.127 mm).  
All specifications are to the latest revisions. Specifications are subject to change without notice.  
Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

T:\Release\DataSheets\FlukeDataSheet's5018\_1\_01.doc

**Sales: 909-469-2900 Fax: 909-629-3317**

**Technical Assistance: 800-241-2060**

PomonaACCESS 90294 (800) 444-6785 or (949) 253-3858

More drawings available at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

Page 2 of 2