Product data sheet Characteristics

8501KPDR12V53

Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, 8 pin, DPDT, 2 NO, 2 NC, 24 VDC coil

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price*: 47.58 USD



Main

Man		
Product range	8501K	
Product type	Relay	,
Relay Type	General purpose	
Mounting type	Socket	
Contact composition	DPDT	1140
[Uc] control circuit voltage	24 V DC	
Pilot light	No indicator	
Manual operator	Without test button	

Complementary

Complementary		
Horsepower rating	1 hp 277 V AC 0.33 hp 120 V AC	
Breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 277 V AC resistive control circuit UL 508 10 A 30 V DC resistive control circuit UL 508	hetii ii do for o o
Maximum switching voltage	300 V AC 30 V DC	
Contact material	Silver alloy (AgNi)	9
Operating time	20 ms - pick-up 20 ms - drop-out	• • •
Shape of pins	Tubular	
For use with	8501NR52 8501NR51	i de la companya de l

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Ambient temperature range - operational	-40131 °F (-4055 °C)
Product certifications	UL Listed UL Recognized CSA CE
Maximum Height	2.66 in (67.56 mm)
Maximum Width	1.4 in (35.56 mm)
Maximum Depth	1.4 in (35.56 mm)

Ordering and shipping details

or dorning daries or ripping doctors		
Category	21141 - 8501 KP	
Discount Schedule	CP2	
GTIN	00785901278177	
Nbr. of units in pkg.	1	
Package weight(Lbs)	3.20 oz (90.718 g)	
Returnability	Yes	
Country of origin	CN	

Packing Units


Unit Type of Package 1	PCE
Package 1 Height	1.70 in (4.318 cm)
Package 1 width	1.70 in (4.318 cm)
Package 1 Length	3.00 in (7.62 cm)

Offer Sustainability

Sustainable offer status	Green Premium product WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
California proposition 65		
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	

8501KPDR12V53

Approximate Dimensions




Product data sheet Connections and Schema

8501KPDR12V53

Connections and Wiring Diagrams

8501KP12•••



IEC