TINA2-RS

~14° spot beam. Assembly with holder and installation tape.




TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16 mm
Height	9.5 mm
Fastening	tape, pin
Colour	black
Box size	451 x 241 x 298 mm
Box weight	8.3 kg
Quantity in Box	4140 pcs
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
TINA2-RS	Lens	PMMA	clear
TINA2-HLD-BLK	Holder	PC	black
TINA-TAPE3	Tape	PU tape	black


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



Bottom view



Front view



Top view

INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C12372	TINA2-HLD-BLK	PC	black
2	-	TINA2-XP lens	PMMA	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
TINA2-XP series

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE A4

PART NUMBER -

SCALE 1:1 WEIGHT 1,7 g SHEET 1/1


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

CREE

LED	XB-H
FWHM	17.0°
Efficiency	86 %
Peak intensity	8.700 cd/lm
Required components:	






CREE

LED	XQ-E HI
FWHM	9.0°
Efficiency	81 %
Peak intensity	25.000 cd/lm
Required components:	






LUMILEDS


LED	LUXEON TX
FWHM	15.0°
Efficiency	89 %
Peak intensity	9.860 cd/lm
Required components:	





NICHIA

LED	NVSxx19B/NVSxx19C
FWHM	18.0°
Efficiency	88 %
Peak intensity	7.000 cd/lm
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NWSx229A
FWHM	25.0°
Efficiency	86 %
Peak intensity	3.600 cd/lm
Required components:	





OSRAM
Opto Semiconductors

LED	Oslon Square EC
FWHM	13.0°
Efficiency	88 %
Peak intensity	9.300 cd/lm
Required components:	

OSRAM
Opto Semiconductors

LED	Oslon Square PC
FWHM	12.0°
Efficiency	88 %
Peak intensity	9.210 cd/lm
Required components:	

OSRAM
Opto Semiconductors

LED	Oslon SSL 150
FWHM	11.0°
Efficiency	90 %
Peak intensity	19.500 cd/lm
Required components:	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (MEASURED):

OSRAM Opto Semiconductors

LED	Oslon SSL 80
FWHM	10.0°
Efficiency	88 %
Peak intensity	16.000 cd/lm

Required components:

OSRAM Opto Semiconductors

LED	SFH 4715S
FWHM	14.0°
Efficiency	%
Peak intensity	cd/lm

Required components:

OSRAM Opto Semiconductors

LED	SFH 4716S
FWHM	11.0°
Efficiency	%
Peak intensity	cd/lm


Required components:

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

LUMILEDS

LED	LUXEON C
FWHM	11.0°
Efficiency	92 %
Peak intensity	14.000 cd/lm
Required components:	




LUMILEDS

LED	LUXEON IR Compact
FWHM	10.0°
Efficiency	84 %
Peak intensity	0.000 cd/lm
Required components:	


NICHIA

LED	NFSx757G
FWHM	10.0°
Efficiency	93 %
Peak intensity	16.690 cd/lm
Required components:	



OSRAM
Opto Semiconductors

LED	Oslon Black Flat
FWHM	8.6°
Efficiency	92 %
Peak intensity	32.400 cd/lm
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED	Oslon Square Flat
FWHM	11.0°
Efficiency	91 %
Peak intensity	16.400 cd/lm
Required components:	






OSRAM
Opto Semiconductors

LED	SFH 4770S
FWHM	16.0°
Efficiency	87 %
Peak intensity	9.200 cd/lm
Required components:	


OSRAM
Opto Semiconductors

LED	Synios P2720 1 mm
FWHM	10.0°
Efficiency	92 %
Peak intensity	20.340 cd/lm
Required components:	



OSRAM
Opto Semiconductors

LED	Synios P2720 1/2 mm
FWHM	9.0°
Efficiency	92 %
Peak intensity	24.030 cd/lm
Required components:	




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED	Synios P2720 1/4 mm
FWHM	8.0°
Efficiency	92 %
Peak intensity	27.470 cd/lm

Required components:



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.