


SCHEMATIC (NON-SHORTING)



SK-22F01-GXXX

手柄
G-Switch P/N

Switch Height (mm)

G020=2.0	G030=3.0
G040=4.0	G050=5.0
G055=5.5	G060=6.0
G065=6.5	G070=7.0
G075=7.5	G080=8.0
G085=8.5	G090=9.0
G095=9.5	G100=10.0

G-Switch Specification:

- Electrical Specifications: 1.0A/DC24V
- Contact resistance (CR): $\leq 50\text{m}\Omega$
- Insulation Resistance(IR): $\geq 100\text{M}\Omega$ DC250V
- Compressive strength (WV): AC250V 1minute
- Operating temperature: $-25^{\circ}\text{C}\sim+70^{\circ}\text{C}$
- Storage humidity: $<85\%\text{RH}$
- Electrical life: 10,000Cycles.



G-Switch Electronic (HongKong) CO.,Ltd.

Unless otherwise specified, Tolerance:
 X ± 0.30
 X.X ± 0.20
 X.XX ± 0.15
 X.XXX ± 0.10
 Angles ± 3

DESIGN	Bright Lee	DATE	2016.05.29	Mold code:	
CHECKED		DATE		SK-22F01-GXXX	
APPROVED		DATE			
http://www.dg-switch.com				REV: X1	SCALE: 4:1
TEL:0769-82388879				SIZE: A4	SHEET: 1/1



ROHS Compliant 2002/95/EC



Halogen Free



Process Capable