



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1030 MHz (BW 2MHz) SMD 3X3 mm

TST Part No.: TA2541A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Michael Yang *Michael*

Approval by: _____ Andy Yu *Andy Yu*

Date: _____ 2019/05/17

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1030MHz

MODEL NO.:TA2541A

REV. NO.:1.0

A. MAXIMUM RATING:

1. Input Power Level: 20 dBm
2. DC Voltage : 6V
3. Operating Temperature: -20℃ to +60℃
4. Storage Temperature: -40℃ to +85℃
5. Moisture Sensitive Level (MSL): Level 1

RoHS Compliant
Lead free
Lead-free soldering

Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (single) : $Z_s = 50 \Omega$

Terminating load impedance (single) : $Z_L = 50 \Omega$


Item	Unit	Min	Type.	Max
Center Frequency Fc	MHz	-	1030.	-
Insertion Loss (1029~1031 MHz) IL	dB		3.0	4.0
VSWR (1029~1031 MHz)			1.5	2.0
Amplitude ripple				
(1029~1031 MHz)	dB		0.5	1.2
Attenuation				
1024.5 ~ 1035.5 MHz	dB	4	5	23~ 27℃
1020 ~ 1041 MHz	dB	25	30	23~ 27℃
1015 ~ 1045 MHz	dB	35	40	23~ 27℃
1005 ~ 1055 MHz	dB	45	50	
990 ~ 1070 MHz	dB	50	55	
Temperature coefficient	ppm/℃	-36		
Package size	mm	SMD 3x3		

C... TEST CIRCUIT:


(2): Unbalance Port

(5): Unbalance Port


Others: Ground




D. Frequency Characteristics: S21 response :(Span 200MHz)




S21 response :(Span 20MHz)



S21 response :(Span 3GHz)




E. OUTLINE DRAWING:



Unit : mm

Not Specified Tolerance : ± 0.15 mm



Pin No.	Symbol	Function
1	GND	Ground
2	IN	Input
3	GND	Ground
4	GND	Ground
5	OUT	Output
6	GND	Ground

Data code : See the table

WK	01	02	...	26	27	28	...	52
Code	A	B	...	Z	a	b	...	z


△ Year code : See the table

Year	2008	2009	2010	2011	...	2019	2020
Code	8	9	0	1	...	9	0

F. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)





G.

- 1.
- 2.
- 3.
- 4.

