

N-Channel Enhancement Mode Power MOSFET


MTA50N15J3

BV_{DSS}	150V
I_D@T_C=25°C, V_{GS}=10V	27A
R_{DS(ON)}@V_{GS}=10V, I_D=15A	44.3 mΩ (typ)
R_{DS(ON)}@V_{GS}=4.5V, I_D=10A	43.0 mΩ (typ)


Features

- Low On Resistance
- Simple Drive Requirement
- Low Gate Charge
- Fast Switching Characteristic
- RoHS compliant package

Symbol




Outline



Ordering Information

Device	Package	Shipping
MTA50N15J3-0-T3-X	TO-252 (Pb-free lead plating package)	2500 pcs / Tape & Reel



**Absolute Maximum Ratings** ($T_C=25^{\circ}\text{C}$)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage (Note 1)		V _{DS}	150	V
Gate-Source Voltage		V _{GS}	±20	
Continuous Drain Current @T _C =25°C, V _{GS} =10V (Note 1)		I _D	27	A
Continuous Drain Current @T _C =100°C, V _{GS} =10V (Note 1)			19	
Continuous Drain Current @T _A =25°C, V _{GS} =10V (Note 4)		I _{DSM}	4.0	
Continuous Drain Current @T _A =70°C, V _{GS} =10V (Note 4)			3.2	
Pulsed Drain Current @ V _{GS} =10V (Note 3)		I _{DM}	100	
Avalanche Current @L=0.1mH (Note 3)		I _{AS}	13	
Single Pulse Avalanche Energy @ L=1mH, I _D =13 Amps, V _{DD} =50V (Note 5)		E _{AS}	84	mJ
Power Dissipation	T _C =25°C (Note 1)	P _D	100	W
	T _C =100°C (Note 1)		50	
	T _A =25°C (Note 2)	P _{DSM}	2	
	T _A =70°C (Note 2)		1.3	
Operating Junction and Storage Temperature		T _j , T _{stg}	-55~+175	°C/W

*Drain current limited by maximum junction temperature

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{th,j-c}$	1.5	$^{\circ}\text{C/W}$
Thermal Resistance, Junction-to-ambient, max (Note2)	$R_{th,j-a}$	62.5	
Thermal Resistance, Junction-to-ambient, max (Note4)		90	

Note : 1. The power dissipation P_D is based on $T_{J(MAX)}=175^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.2. The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C . The value in any given application depends on the user's specific board design.3. Pulse width limited by junction temperature $T_{J(MAX)}=175^{\circ}\text{C}$. Ratings are based on low frequency and low duty cycles to keep initial $T_J=25^{\circ}\text{C}$.4. When mounted on the minimum pad size recommended (PCB mount), $t \leq 10\text{s}$.5. 100% tested by conditions of $L=0.1\text{mH}$, $I_{AS}=5\text{A}$, $V_{GS}=10\text{V}$, $V_{DD}=25\text{V}$


**Characteristics (T_j=25°C, unless otherwise specified)**

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	150	-	-	V	V _{GS} =0V, I _D =250μA
ΔBV _{DSS} /ΔT _j	-	0.1	-	V/°C	Reference to 25°C, I _D =250μA
V _{GS(th)}	0.5	-	1.2	V	V _{DS} = V _{GS} , I _D =250μA
*G _{FS}	-	43.5	-	S	V _{DS} =10V, I _D =10A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V
I _{DSS}	-	-	1	μA	V _{DS} =120V, V _{GS} =0V
	-	-	25		V _{DS} =120V, V _{GS} =0V, T _j =125°C
*R _{DS(ON)}	-	44.3	56	mΩ	V _{GS} =10V, I _D =15A
	-	43.0	56		V _{GS} =4.5V, I _D =10A
Dynamic					
*Q _g	-	69.9	-	nC	I _D =15A, V _{DS} =120V, V _{GS} =10V
*Q _{gs}	-	3.8	-		
*Q _{gd}	-	12.5	-		
*t _{d(ON)}	-	11.6	-	ns	V _{DS} =75V, I _D =15A, V _{GS} =10V, R _G =6Ω
*t _r	-	21	-		
*t _{d(OFF)}	-	108.2	-		
*t _f	-	83.8	-		
C _{iss}	-	2161	-	pF	V _{GS} =0V, V _{DS} =80V, f=1MHz
C _{oss}	-	96	-		
C _{rss}	-	19	-		
R _g	-	1	-	Ω	f=1MHz
Source-Drain Diode					
*I _S	-	-	27	A	
*I _{SM}	-	-	100		
*V _{SD}	-	0.8	1.2	V	I _S =15A, V _{GS} =0V
*t _{rr}	-	41	-	ns	V _{GS} =0V, I _F =15A, dI _F /dt=100A/μs
*Q _{rr}	-	85	-	nC	


*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%

Typical Characteristics


Static Drain-Source On-State resistance vs Drain Current




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State Resistance vs Gate-Source Voltage




Reverse Drain Current vs Source-Drain Voltage



Capacitance vs Drain-to-Source Voltage




Drain-Source On-State Resistance vs Junction Tempearture




Typical Characteristics(Cont.)


Forward Transfer Admittance vs Drain Current




Normalized Threshold Voltage vs Junction Temperature




Maximum Safe Operating Area




Gate Charge Characteristics




Maximum Drain Current vs Case Temperature




Single Pulse Maximum Power Dissipation




Typical Characteristics(Cont.)




Recommended soldering footprint


Unit ($\frac{\text{mm}}{\text{inch}}$)

Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T_{smax} to T_p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T_{smin})	100°C	150°C
-Temperature Max(T_{smax})	150°C	200°C
-Time(t_{smin} to t_{smax})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T_L)	183°C	217°C
- Time (t_L)	60-150 seconds	60-150 seconds
Peak Temperature(T_p)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t_p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-252 Dimension



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	e	0.086	0.094	2.186	2.386
A1	0.000	0.005	0.000	0.127	e1	0.172	0.188	4.372	4.772
B	0.039	0.048	0.990	1.210	H	0.163	REF	4.140	REF
b	0.026	0.034	0.660	0.860	K	0.190	REF	4.830	REF
b1	0.026	0.034	0.660	0.860	L	0.386	0.409	9.800	10.400
C	0.018	0.023	0.460	0.580	L1	0.114	REF	2.900	REF
C1	0.018	0.023	0.460	0.580	L2	0.055	0.067	1.400	1.700
D	0.256	0.264	6.500	6.700	L3	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	P	0.026	REF	0.650	REF
E	0.236	0.244	6.000	6.200	V	0.211	REF	5.350	REF

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
 - CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.