



Datasheet

Multi-rate SFP Interfaces



Features

- Support for protocols from 100 Mbps to 4.25 Gbps
- Multi-rate support for Gigabit Ethernet, Fiber Channel, and 4-Gigabit Fiber Channel
- Digital Diagnostic SFF-8472 compliant
- SFP MSA SFF-8074i compliance
- GR 253/STM G.957 compliance
- Bellcore GR-468 compliance
- Low jitter
- Hot plug-in support
- Low EMI metal enclosure
- Class 1 laser
- RoHS compliance
- 21 CFR 1040.10 and 1040.11 compliance (may carry "UL", "TUV", or "CSA" laboratory certifications)

Overview

Small Form-Factor Pluggable (SFP) interfaces from MRV Communications provide flexible high speed links in a small industry standard package. They deliver the deployment options and inventory control that network administrators demand for growing networks.

SFPs are designed to Multi-Source Agreement (MSA) standards to ensure network equipment compatibility. They are a perfect addition to the MRV Communications line of Fiber Driver® pluggable media modules and chassis, and they compliment the OptiSwitch® line of routers and switches. With other MRV modular products, they define the ultimate in managed fiber optic networks.

Visit the MRV website at www.mrv.com or contact your nearest authorized MRV Communications dealer for more information.

Ordering Information

Model	Description	Protocol (Mbps)	Wavelength (nm)	Output Power (dBm)		Min. Receiver Sensitivity (dBm)	Min. Link Budget (dBm)**	Saturation Power (dBm)	BER	Data Rate	Supply Voltage (V)	Oper. Temp. Range (°C)	Digital Diagnostics	Distance Range (km)***
				Min	Max									
SFP-MR2-M	SFP Multi-mode	Multi-rate 100-200	1310	-22	-14	-29	DL*	-14	1.0E ⁻¹² 1.00E ⁻¹⁰ 1.00E ⁻¹⁵	125 Mbps 155 Mbps 200 Mbps	3.3	0 to 70	No	0 - 2
SFP-MR27D-MMX	SFP Multi-mode Extender	Multi-rate 100-2700	1310	-10	-3	-20	DL*	-3	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	0 - 1
SFP-MR27D-SR1	SFP Single-mode	Multi-rate 100-2700	1310	-10	-3	-20	10	-3	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	0 - 20
SFP-MR27D-IR1	SFP Single-mode	Multi-rate 100-2700	1310	-5	0	-20	14	0	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	0 - 28
SFP-MR27D-IR2	SFP Single-mode	Multi-rate 100-2700	1550	-5	0	-20	14	0	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	0 - 56
SFP-MR27D-LR1	SFP Single-mode	Multi-rate 100-2700	1310	-2	3	-27	24	-9	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	20 - 48
SFP-MR27D-LR2	SFP Single-mode	Multi-rate 100-2700	1550	-2	3	-28	24	-9	1.00E ⁻¹⁰ 1.00E ⁻¹²	SONET 1.25 Gbps	3.3	0 to 70	Yes	40 - 96

* DL - Dispersion Limited

** Dispersion penalty may apply

*** Maximum range quoted not possible with all wavelengths and/or fiber. Please consult MRV.


Ordering Information

Model	Description	Protocol	Wavelength (nm)	Output Power (dBm)		Min. Receiver Sensitivity (dBm)	Min. Link Budget (dBm)**	Saturation Power (dBm)	BER	Data Rate (Gbps)	Oper. Temp. Range (°C)	Digital Diagnostics	Distance Range (km)***
				Min	Max								
SFP-DGD-SX	Dual Rate SFP, Multi-mode	GbE/1 Gbps FC/ 2.1 Gbps FC	850	-10	-2	-18	DL*	0	1.00E ⁻¹²	2.125	-20 to 85	Yes	0 - 0.50
SFP-TGD-SX	Triple Rate SFP, Multi-mode	1.063/2.125/4.25 Gbps FC/1.25 Gbps GbE	850	-10	-2	-15	DL*	0	1.00E ⁻¹²	4.25	-20 to 85	Yes	0 - 0.50
SFP-DGD-LX	Dual Rate SFP, Single-mode	GbE/1 Gbps FC/ 2.1 Gbps FC	1310	-10	-3	-21	10	0	1.00E ⁻¹²	2.125	-40 to 85	Yes	0 - 10
SFP-TGD-SR4	Triple Rate SFP, Single-mode	1.063/2.125/4.25 Gbps FC/1.25 Gbps GbE	1310	-10	3	-18	8	0	1.00E ⁻¹²	4.25	-20 to 85	Yes	0 - 10 (1GFC) 0 - 4 (4GFC)

* DL - Dispersion Limited

** Dispersion penalty may apply

*** Maximum range quoted not possible with all wavelengths and/or fiber. Please consult MRV.

MRV has more than 50 offices throughout the world. Addresses, phone numbers, and fax numbers are listed at www.mrv.com. Please e-mail us at sales@mrv.com or call us for assistance.

MRV (West Coast USA)
 20415 Nordhoff St.
 Chatsworth, CA 91311
 800-338-5316
 818-773-0900

MRV (East Coast USA)
 295 Foster St.
 Littleton, MA 01460
 800-338-5316
 978-952-4700

MRV (International)
 Business Park Moerfelden
 Waldeckerstrasse 13
 64546 Moerfelden-Walldorf
 Germany
 Tel. (49) 6105/2070
 Fax. (49) 6105/207-100

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact MRV Communications for more information. MRV Communications and the MRV Communications logo are trademarks of MRV Communications, Inc. Other trademarks are the property of their respective holders.