



Screwless Connectors  
Luminaire Connectors

LK 980-01 RZ/ 3 printed "N Earth L"

Terminal Block, 3 pole, Fixing: Catch Pin, Printing: N Earth L, Voltage Rating: 450 V, Current Rating: 24 A, Cross-Section: 2.5 mm<sup>2</sup>, External Connection Type: screwless



Order Info

<b>Reference Number (ref. no.)</b>	045013
<b>Applications</b>	Lighting, Electrical Appliances
<b>PU</b>	500
<b>EAN</b>	4028012100286

Type

<b>Type</b>	Terminal Block
<b>Number of poles</b>	3 pole
<b>Clamping Units per Pole</b>	2
<b>Colour</b>	white
<b>Cross-Section</b>	2.5 mm <sup>2</sup>
<b>Printing</b>	N Earth L

Technical Data

<b>Voltage Rating</b>	450 V
<b>Current Rating</b>	24 A
<b>Insulating Material</b>	PA 6.6
<b>Contact Material</b>	Spring Steel, Copper
<b>Flammability Rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>Stripping Length</b>	8.0-9.0 mm
<b>Internal Core Cross-Section max.</b>	1.5 / 2.5 mm <sup>2</sup>
<b>External Core Cross-Section min.</b>	0.5 mm <sup>2</sup>
<b>External Core Cross-Section max.</b>	2.5 mm <sup>2</sup>
<b>Fixing</b>	Catch Pin
<b>External Connection Type</b>	screwless
<b>Internal Core Cross-Section min.</b>	0.5 mm <sup>2</sup>
<b>Type of Conductor Solid External</b>	yes
<b>Type of Conductor Flexible External</b>	yes
<b>Type of Conductor Stranded External</b>	yes
<b>Type of Conductor Solid Internal</b>	yes

<b>Type of Conductor Stranded Internal</b>	yes
<b>Approbation EN60998</b>	LK980-01_EN60998_20070627_20101213_VDE_ENEC_40021343_v
<b>Approbation UL</b>	LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf

## Accessories

<b>ZEL 110</b>	196420
<b>ZEL 900</b>	196423