






LOC	DIST	REVISIONS				
		REV	LTR	DESCRIPTION	DATE	DWN APVD
CM	00	AN2	REVISED	PER ECO-11-004587	11MAR11	RK HMR


1. MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK® PLUG.
2. RECOMMENDED PANEL THICKNESS 0.76 - 2.29.
3. PANEL MUST BE PUNCHED SO THAT THE HOUSING ENTERS THE PANEL IN THE SAME DIRECTION AS THE PUNCH.
4. OPTIONAL FOR KEYING HOUSING IN PANEL.
5. CIRCUIT NUMBER 1 LOCATION.
6. DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.
7. FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, NO RIBS OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.
8. UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE EACH ON SIDE OF HOUSING.
9. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



DETAIL A
OPTIONAL CONSTRUCTIONS



RECOMMENDED PANEL CUT OUT



3-DIMENSIONAL MODEL
NTS

4.45	.175	27.43	1.080
2.79	.110	20.70	.815
2.54	.100	20.32	.800
2.41	.095	13.46	.530
2.29	.090	13.21	.520
0.76	.030	8.64	.340
0.38	.015	8.13	.320
0.25	.010	7.62	.300
0.13	.005	6.35	.250
MM	IN	MM	IN

CONVERSION TABLE

BLACK	1-480701-9
GRAY	1-480701-8
BLUE	1-480701-6
GREEN	1-480701-5
YELLOW	1-480701-4
ORANGE	1-480701-3
RED	1-480701-2
BROWN	1-480701-1
NATURAL	1-480701-0
COLOR	PART NO.

9 OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
K. WHITAKER
28JUL2004
CHK
S. RIDGILL
28JUL2004
APVD
S. RIDGILL
28JUL2004

DIMENSIONS:
mm

0. PLC ± -
1. PLC ± -
2. PLC ± 0.13
3. PLC ± -
4. PLC ± -
ANGLES ± 0°30'

MATERIAL
NYLON, UL94V-2

FINISH
-

PRODUCT SPEC
APPLICATION SPEC
WEIGHT
-

SIZE
A1

CAGE CODE
00779

DRAWING NO
480701

NAME
CAP,
3 CIRCUIT,
UNIVERSAL MATE-N-LOK(TM)

RESTRICTED TO
-

CUSTOMER DRAWING

SCALE
4:1

SHEET
1 OF 2


REV
AN2

TE Connectivity





TE



LOC	DIST	REVISIONS				
CM	00	P	LTR	DESCRIPTION	DATE	OWN
		-	-	SEE SHEET 1	-	-




- 1 . STAMP NUMBERS 3.18 HIGH AT WIRE END OF HOUSING (12 POINT DAVID TYPE).
- 2 . CHARACTERS TO BE STAMPED ON HOUSING IN A MANNER AS TO BE READ FROM WIRE END ONLY.
- 3 . VIOLET, BLACK, BROWN AND BLUE COLORED BLOCKS TO BE STAMPED WITH WHITE CHARACTERS. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTERS.



5.59	.220	-	-
4.70	.185	27.43	1.080
3.18	.125	20.32	.800
0.38	.015	13.21	.520
0.25	.010	8.13	.320
0.13	.005	7.62	.300
MM	IN	MM	IN

CONVERSION TABLE



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± 0.13
3 PLC ± -
4 PLC ± -
ANGLES ± 0°30'
FINISH -

DWN
K. WHITAKER
28JUL2004

CHK
S. RIDGILL
28JUL2004

APVD
S. RIDGILL
28JUL2004

NAME

CAP,
3 CIRCUIT,
UNIVERSAL MATE-N-LOK(TM)

SIZE
A1

CAGE CODE
00779

DRAWING NO
480701

RESTRICTED TO
-

TE Connectivity

CUSTOMER DRAWING

SCALE
4:1

SHEET
2

OF
2

REV
AN2