ALPHA & OMEGA SEMICONDUCTOR


AO4472
N-Channel Enhancement Mode Field Effect Transistor

General Description


The AO4472 uses advanced trench technology to provide excellent $R_{DS(ON)}$, shoot-through immunity, body diode characteristics and ultra-low gate resistance. This device is ideally suited for use as a low side switch in Notebook CPU core power conversion. *Standard Product AO4472 is Pb-free (meets ROHS & Sony 259 specifications). AO4472L is a Green Product ordering option. AO4472 and AO4472L are electrically identical.*

Features

V_{DS} (V) = 30V
I_D = 19A (V_{GS} = 10V)
$R_{DS(ON)}$ < 5.2mΩ (V_{GS} = 10V)
$R_{DS(ON)}$ < 7.2mΩ (V_{GS} = 4.5V)



SOIC-8



Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current [A]	T_A=25°C	I_D	19	A
	T_A=70°C		16	
Pulsed Drain Current [B]		I_{DM}	80	
Power Dissipation	T_A=25°C	P_D	3	W
	T_A=70°C		2.1	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	31	40	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		59	75	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	16	24	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V	30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=24V, V_{GS}=0V			1	µA
		T_J=55°C			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}= ±20V			100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250µA	1	1.9	2.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=10V, V_{DS}=5V	80			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=19A		4.3	5.2	mΩ
		T_J=125°C		6.1	7.5	
		V_{GS}=4.5V, I_D=15A		6	7.2	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=19A		82		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.7	1	V
I_S	Maximum Body-Diode Continuous Current				4.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz		6060	7270	pF
C_{oss}	Output Capacitance			638	960	pF
C_{rss}	Reverse Transfer Capacitance			355	530	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		0.45	0.9	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=15V, I_D=19A	80	103	124	nC
Q_g(4.5V)	Total Gate Charge		37	48	58	nC
Q_{gs}	Gate Source Charge			18		nC
Q_{gd}	Gate Drain Charge			15		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=0.8Ω, R_{GEN}=3Ω		12	16	ns
t_r	Turn-On Rise Time			8	12	ns
$t_{D(off)}$	Turn-Off DelayTime			51.5	70	ns
t_f	Turn-Off Fall Time			8.8	14	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=19A, dI/dt=100A/µs		33.5	44	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=19A, dI/dt=100A/µs		22	30	nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using 80 µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev 0: May 2006

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance