



Part No.

# QSQS-HOS-50ft

*Quick-test 6900 psi hose, S.S. hose ends, 50 ft (15.2 m) long (with hose reel)*

Microbore hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

## Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required – connect to adapters without wrenches, thread sealant or thread tape
- Bubble tight connections to 6900 psi (475 bar) with no moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- Silver color dramatically reduces the effect that changing temperature has on pressure stability
- A corrosion resistant strain-relief on each hose end reduces wear and dramatically increases hose life
- Hose is pin-pricked for use in Natural Gas applications
- Made in U.S.A.

## Specifications

|                     |   |
|---------------------|---|
| Length              | 50 ft   |
| Pressure Range      | 0 to 6900 psi (0 to 475 bar)  |
| Burst Pressure      | 27000 psi (1,860 bar)   |
| End 1               | Female Quick-test, stainless steel  |
| End 2               | Female Quick-test, stainless steel  |
| Temperature range   | -40 to 140 °F (-40 to 60 °C)  |
| Outer Diameter      | 0.2 in (5.1 mm)   |
| Inner Diameter      | 0.08 in (2.0 mm)  |
| Minimum Bend Radius | 1 in (25.4 mm)  |
| Color               | Silver  |
| Construction        | Polyamide core tube, High tensile synthetic fiber and polyamide outer cover |
| End materials       | Stainless Steel   |
| Fluid Media         | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water                     |