
PART NUMBER	SSF-LXH42103LI4G4D	REV.	А
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
10.17.95	UPDATED SPECS, ADDED NOTE 4.		Α

	16.76 [0.660] MAX.	-
1.90 [0.075] —	4.32 [0.170] (3 PLS.)	
	5 7-	5.08 [0.200]
	2 4 6 8-	5.08
ANODE TYP. THIS SIDE		0.50 [0.020] T/P
	2.54 [0.100] (4 PLS.)	0.30 [0.012] TYP.



ELECTRO-OPTICAL CHARAC	TERISTICS TA = 25°C	I <sub>f</sub> = 20mA		
PARAMETER	GREEN	RED	UNITS	TEST COND
PEAK WAVELENGTH	565	635	nm	
FORWARD VOLTAGE (TYP)	2.2	2.2	nm	
FORWARD VOLTAGE (MAX)	2.5	2.5	$V_{f}$	
REVERSE VOLTAGE	5.0	5.0	$V_r$	I <sub>r</sub> =100uA
AXIAL INTENSITY	1.0	1.0	mcd	I <sub>f</sub> =20mA
LED POSITION:	2,4,6,8	1,3,5,7		
EPOXY LENS FINISH:	DIFFUSED SAME AS	COLOR		

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*	(G/R)	150	mA
STEADY CURRENT	(G/R)	25/30	mA
POWER DISSIPATION	(G/R)	105	mW
DERATE FROM 25°C		-1.2	mW/*C
OPERATING TEMP.		-40 TO +85	*C
STORAGE TEMP.		-40 TO +85	*C
SOLDERING TEMP.		+260	*C
2.0mm FROM BODY			3 SEC. MAX

\* t<10uS

RELIABILITY NOTE:
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION
INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

- 1. SSL-LX3044LGD (4 PCS), SSL-LX3044LID (4 PC).
  2. SSH-LXH42103 HOLDER. MATERIAL: BLACK NYLON, UL 94V-0.
- TOLERANCES: ±0.51 (±0.020).
- 4. PARTS TO BE SUPPLIED IN TUBES.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

T-1, 8 LED, RIGHT ANGLE, DIFFUSED LENS, LED FAULT INDICATOR, LOW CURRENT SELECTION.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

00.00.00 DATE: DRAWN BY: SS PAGE: 1 OF 1 CHKD BY: SCALE: APRVD BY: UNIT: mm [INCH] (Pb)