


ZWD225PAF-0524/A



<b>Sales Region</b>	Worldwide
<b>Series</b>	ZWD-PAF
<b>Status</b>	Production
<b>Feature</b>	Peak power capability
<b>Option</b>	With cover type
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	83% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>9A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	225W
Total Maximum Peak Power	440W

### Cases Shape & Size

Case shape	PC board
Width(W)	108mm Nom.
Height(H)	58mm Nom.
Depth(D)	252mm Nom.
Weight	1065g Typ.

### Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178
	Den-an

