MOSFET

Metal Oxide Semiconductor Field Effect Transistor

OptiMOS™


OptiMOS™5 Power-MOSFET, 30 V
BSC0502NSI

Data Sheet

Rev. 2.0
Final

Power Management & Multimarket

1 Description



Features

- Optimized for high performance buck converters
- Monolithic integrated Schottky-like diode
- Very low on-resistance $R_{DS(on)}$ @ V_{GS}=4.5 V
- 100% avalanche tested
- N-channel
- Qualified according to JEDEC[1)] for target applications
- Pb-free lead plating; RoHS compliant
- Halogen-free according to IEC61249-2-21




Table 1 Key Performance Parameters

Parameter	Value	Unit
V_{DS}	30	V
$R_{DS(on),max}$	2.3	mΩ
I_D	100	A
Q_{OSS}	13.5	nC
Q_G(0V..4.5V)	9.0	nC

Type / Ordering Code	Package	Marking	Related Links
BSC0502NSI	PG-TDSON-8	0502NSI	-

[1)] J-STD20 and JESD22

Table of Contents

Description 2
Maximum ratings 4
Thermal characteristics 4
Electrical characteristics 5
Electrical characteristics diagrams 7
Package Outlines 11
Revision History 13
Disclaimer 13

2 Maximum ratings

at T_j = 25 °C, unless otherwise specified

Table 2 Maximum ratings

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Continuous drain current	I_D	- - - - -	- - - - -	100 70 100 63 26	A	V_{GS}=10 V, T_C=25 °C V_{GS}=10 V, T_C=100 °C V_{GS}=4.5 V, T_C=25 °C V_{GS}=4.5 V, T_C=100 °C V_{GS}=10 V, T_A=25 °C, R_{thJA}=50 K/W[1)]
Pulsed drain current[2)]	$I_{D,pulse}$	-	-	400	A	T_C=25 °C
Avalanche current, single pulse[3)]	I_{AS}	-	-	45	A	T_C=25 °C
Avalanche energy, single pulse	E_{AS}	-	-	14	mJ	I_D=45 A, R_{GS}=25 Ω
Gate source voltage	V_{GS}	-20	-	20	V	-
Power dissipation	P_{tot}	- -	- -	43 2.5	W	T_C=25 °C T_A=25 °C, R_{thJA}=50 K/W[1)]
Operating and storage temperature	T_j, T_{stg}	-55	-	150	°C	IEC climatic category; DIN IEC 68-1: 55/150/56

3 Thermal characteristics

Table 3 Thermal characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Thermal resistance, junction - case, bottom	R_{thJC}	-	-	2.9	K/W	-
Thermal resistance, junction - case, top	R_{thJC}	-	-	20	K/W	-
Device on PCB, 6 cm² cooling area[1)]	R_{thJA}	-	-	50	K/W	-

[1)] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.
[2)] See Diagram 3 for more detailed information
[3)] See Diagram 13 for more detailed information

4 Electrical characteristics

Table 4 Static characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Drain-source breakdown voltage	$V_{(BR)DSS}$	30	-	-	V	V_{GS}=0 V, I_D=10 mA
Breakdown voltage temperature coefficient	$dV_{(BR)DSS}/dT_j$	-	15	-	mV/K	I_D=10 mA, referenced to 25 °C
Gate threshold voltage	$V_{GS(th)}$	1.2	-	2	V	V_{DS}=V_{GS}, I_D=250 µA
Zero gate voltage drain current	I_{DSS}	- -	- 0.4	0.5 -	mA	V_{DS}=24 V, V_{GS}=0 V, T_j=25 °C V_{DS}=24 V, V_{GS}=0 V, T_j=125 °C
Gate-source leakage current	I_{GSS}	-	10	100	nA	V_{GS}=20 V, V_{DS}=0 V
Drain-source on-state resistance	$R_{DS(on)}$	- -	2.4 1.9	2.8 2.3	mΩ	V_{GS}=4.5 V, I_D=30 A V_{GS}=10 V, I_D=30 A
Gate resistance	R_G	-	1.4	2.3	Ω	-
Transconductance	g_{fs}	65	130	-	S	|V_{DS}|>2|I_D|$R_{DS(on)max}$, I_D=30 A

Table 5 Dynamic characteristics

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Input capacitance[1)]	C_{iss}	-	1200	1600	pF	V_{GS}=0 V, V_{DS}=15 V, f=1 MHz
Output capacitance[1)]	C_{oss}	-	420	570	pF	V_{GS}=0 V, V_{DS}=15 V, f=1 MHz
Reverse transfer capacitance	C_{rss}	-	44	-	pF	V_{GS}=0 V, V_{DS}=15 V, f=1 MHz
Turn-on delay time	$t_{d(on)}$	-	4	-	ns	V_{DD}=15 V, V_{GS}=10 V, I_D=30 A, $R_{G,ext}$=1.6 Ω
Rise time	t_r	-	4	-	ns	V_{DD}=15 V, V_{GS}=10 V, I_D=30 A, $R_{G,ext}$=1.6 Ω
Turn-off delay time	$t_{d(off)}$	-	19	-	ns	V_{DD}=15 V, V_{GS}=10 V, I_D=30 A, $R_{G,ext}$=1.6 Ω
Fall time	t_f	-	3	-	ns	V_{DD}=15 V, V_{GS}=10 V, I_D=30 A, $R_{G,ext}$=1.6 Ω

[1)] Defined by design. Not subject to production test.

Table 6 Gate charge characteristics[1)]

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Gate to source charge	Q_{gs}	-	3.1	-	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Gate charge at threshold	$Q_{g(th)}$	-	2.0	-	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Gate to drain charge	Q_{gd}	-	2.3	-	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Switching charge	Q_{sw}	-	3.4	-	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Gate charge total	Q_g	-	9.0	12	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Gate plateau voltage	$V_{plateau}$	-	2.5	-	V	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V
Gate charge total[2)]	Q_g	-	19	26	nC	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 10 V
Gate charge total, sync. FET	$Q_{g(sync)}$	-	8.3	-	nC	V_{DS}=0.1 V, V_{GS}=0 to 4.5 V
Output charge[2)]	Q_{oss}	-	13.5	18	nC	V_{DD}=15 V, V_{GS}=0 V


Table 7 Reverse diode

Parameter	Symbol	Values			Unit	Note / Test Condition
		Min.	Typ.	Max.		
Diode continuous forward current	I_S	-	-	50	A	T_C=25 °C
Diode pulse current	$I_{S,pulse}$	-	-	400	A	T_C=25 °C
Diode forward voltage	V_{SD}	-	0.54	0.65	V	V_{GS}=0 V, I_F=5 A, T_j=25 °C
Reverse recovery charge	Q_{rr}	-	15	-	nC	V_R=15 V, I_F=I_S, di_F/dt=400 A/µs

[1)] See ″Gate charge waveforms″ for parameter definition
[2)] Defined by design. Not subject to production test.


5 Electrical characteristics diagrams

Diagram 1: Power dissipation




$P_{tot}=f(T_C)$

Diagram 2: Drain current




$I_D=f(T_C)$; $V_{GS}\geq 10$ V

Diagram 3: Safe operating area




$I_D=f(V_{DS})$; $T_C=25$ °C; $D=0$; parameter: t_p

Diagram 4: Max. transient thermal impedance




$Z_{thJC}=f(t_p)$; parameter: $D=t_p/T$

Diagram 5: Typ. output characteristics




I_D=f(V_{DS}); T_j=25 °C; parameter: V_{GS}

Diagram 6: Typ. drain-source on resistance




$R_{DS(on)}$=f(I_D); T_j=25 °C; parameter: V_{GS}

Diagram 7: Typ. transfer characteristics




I_D=f(V_{GS}); |V_{DS}|>2|I_D|$R_{DS(on)max}$; parameter: T_j

Diagram 8: Typ. forward transconductance




g_{fs}=f(I_D); T_j=25 °C

Diagram 9: Drain-source on-state resistance




$R_{DS(on)}$=f(T_j); I_D=30 A; V_{GS}=10 V

Diagram 10: Typ. gate threshold voltage




$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}

Diagram 11: Typ. capacitances




C=f(V_{DS}); V_{GS}=0 V; f=1 MHz

Diagram 12: Forward characteristics of reverse diode




I_F=f(V_{SD}); parameter: T_j

Diagram 13: Avalanche characteristics




I_{AS}=f(t_{AV}); R_{GS}=25 Ω; parameter: $T_{j(start)}$

Diagram 14: Typ. gate charge




V_{GS}=f(Q_{gate}); I_D=30 A pulsed; parameter: V_{DD}

Diagram 15: Typ. drain-source leakage current




I_{DSS}=f(V_{DS}); V_{GS}=0 V; parameter: T_j

Gate charge waveforms



6 Package Outlines



DIM	MILLIMETERS	
	MIN	MAX
A	0.90	1.10
b	0.31	0.54
b1	0.02	0.22
c	0.15	0.35
D	5.15	5.49
D1	4.95	5.35
D2	3.70	4.40
E	5.95	6.35
E1	5.70	6.10
E2	3.40	3.80
e	1.27	
N	8	
L	0.45	0.71
M	0.45	0.75
Θ	8.5°	12°
aaa	0.25	
eee	0.08	

DOCUMENT NO.
Z8B00003332


SCALE 0 2 0 2 4mm

EUROPEAN PROJECTION

ISSUE DATE
10-04-2013

REVISION
04

Figure 1 Outline PG-TDSON-8, dimensions in mm



Dimension in mm

Figure 2 Outline TDSON-8 Tape

Revision History

BSC0502NSI

Revision: 2015-07-13, Rev. 2.0

Previous Revision		
Revision	Date	Subjects (major changes since last revision)
2.0	2015-07-13	Release of final version

We Listen to Your Comments
Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to:
erratum@infineon.com

Published by
Infineon Technologies AG
81726 München, Germany
© 2015 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.