

# OPS500-501-H NEW

Open Pluggable Specification (OPS) 4K Digital Signage Player with 7th/6th Gen Intel® Core™ i7/i5/i3 & Celeron® Processor and Intel® H110 Chipset

## Features

- Intel® Open Pluggable Specification (OPS compliance)
- 7th/6th gen Intel® Core™ i7/i5/i3 & Celeron® processor (Skylake/Kaby Lake)
- DDR4-2133/2400 SO-DIMM, up to 16GB
- 1 PCIe Mini Card slot
- Easy installation and maintenance
- HDMI for 2nd ultra HD display with 4K@60 Hz resolution




## Specifications


Main System	CPU	LGA1151 socket 7th/6th generation Intel® Core™ and Celeron® processor
	Chipset	Intel® H110
	System Memory	6th generation Intel® Core™: 1 x 260-pin DDR4-2133 SO-DIMM, up to 16GB 7th generation Intel® Core™: 1 x 260-pin DDR4-2133/2400 SO-DIMM, up to 16GB
	Storage	1 x 2.5" SATA HDD tray 1 x mSATA (Option)
	Watchdog Timer	255 levels, 1 ~ 255 sec.
I/O	2 x USB 3.0	
	1 x USB 2.0	
	1 x 10/100/1000 Mbps Ethernet (Intel® i219LM)	
	1 x HDMI with 4K resolution	
	1 x RS-232 (COM 2)	
	1 x Power on/off button	
	1 x Reset button	
	1 x Audio (Line-out)	
	1 x Audio (Mic-in)	
	1 x DisplayPort (4K@60 Hz via OPS JAE interconnector)	
	1 x HDMI 2.0 (4K@60 Hz via OPS JAE interconnector)	
	2 x USB 2.0 (via OPS JAE interconnector)	
	1 x USB 3.0 (via OPS JAE interconnector)	
	1 x Audio (Line-out, via OPS JAE interconnector)	
1 x UART (TX/RX, via OPS JAE interconnector) (COM 1)		
1 x 12 VDC power input by adapter option		
Indicator	1 x LED for system power on	
	1 x LED for HDD active	
WiFi	802.11 b/g/n (optional)	
Expansion Slot	1 x full-size PCIe Mini Card (USB + PCI Express + SATA Signal)	
Dimensions	200 mm (7.87") (W) x 119 mm (4.68") x 30 mm (1.18")	
Packing Dimension	270 mm (10.63") (W) x 197 mm (7.76") x 70mm (2.76")	
Weight (net/gross)	1 kg (2.21 lb)/1.5 kg (3.3 lb)	
Environmental	0°C ~ +45°C (+32°F ~ +113°F) (with airflow 1.2m/s)	

## Packing

- 1 x Driver CD
- 1 x Thermal grease
- 2 x M2 x 5 screw
- 2 x M4 x 6 screw



- |                     |                     |                       |
|---------------------|---------------------|-----------------------|
| 1. JAE TX-25A       | 6. Power switch     | 11. USB 2.0           |
| 2. Optional antenna | 7. Reset            | 12. USB 3.0 x 2       |
| 3. RS-232           | 8. HDD indicator    | 13. Optional antenna  |
| 4. Ethernet         | 9. Audio (Line-out) | 14. 2.5" SATA HDD     |
| 5. HDMI output      | 10. Audio (Mic-in)  | 15. 12VDC power input |



## Optional OS Installation

Windows® 8.1, Windows® 10

## Ordering Information

### Standard

OPS500-501-H	OPS 4K digital signage player with LGA1151 socket Intel® Core™ i7/i5/i3 & Celeron® processor
--------------	--

### Optional

AX93167	OPS docking board with 4K solution
AX93190	OPS docking board with 4K/60 Hz solution

\* Specifications and certifications may vary contingent on options.

## Dimensions

