

VS50E-12



Sales Region	Worldwide
Series	VS-E
Status	Production
Feature	
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 132V
Input Voltage Range[DC]	
Efficiency	85% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.8 to 13.2V
Maximum Output Current	4.3A
Maximum Output Power	51.6W

Cases Shape & Size

Case'□ shape	PC board
Width(W)	50mm Nom.
Height(H)	23mm Nom.
Depth(D)	132mm Nom.
Weight	150g Typ.

Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an Appendix 12
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.