

Data sheet | Item number: 706-2400/201-300

System cable; for Siemens S7-400; 8 digital outputs for higher voltages;
Length: 3 m; Conductor cross-section: 0.34 mm²



www.wago.com/706-2400/201-300



Data Notes

| | |
|------|--|
| Note | If less than 3 channels used at the same time, the maximum current per wire 2 A and up to 5 A (amb. T 30 °C) or 3.5 A (amb. T 50 °C) on the power supply pins N/L. If more than 3 channels used at the same time, the maximum current per wire 0.75 A and up to 5 A (amb. T 30 °C) or 3.5 A (amb. T 50 °C) on the power supply pins N/L. |
|------|--|

Electrical data

| | |
|-------------------------|---------------------------------------|
| Inputs/outputs | 8 digital inputs; for higher voltages |
| Operating voltage | ≤ AC/DC 250 V |
| Current per wire (max.) | 0.75 A |

Connection data

| | |
|-------------------------------|-----------------------------|
| Compatible PLC Modules | Siemens S7-400 |
| Compatible PLC I/O Card Types | 6ES7 422-1FF00-0AA0 |
| Connection type (1) | System |
| Pole number 1 | 20 |
| Pluggable connectors | WAGO 231 Series |
| Connection type 2 | System |
| Pole number 2 | 20 |
| Connector 2 | Siemens 6ES7-492-1BL00-0AA0 |
| Pole number 3 | 48 |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



| | |
|--------------------|----------------------|
| Cable type | LiYY |
| Wire cross-section | 0.14 mm ² |
| Color code | per DIN VDE 47100 |

Physical data

| | |
|--------------|-----|
| Cable length | 3 m |
|--------------|-----|

Material data

| | |
|--------|-------|
| Weight | 1.1 g |
|--------|-------|

Environmental requirements

| | |
|---|---------------|
| Surrounding air temperature (operation) | -20 ... 50 °C |
|---|---------------|

Commercial data

| | |
|----------------|---------------|
| PU (SPU) | 1 Stück |
| Packaging type | box |
| GTIN | 4055143037563 |

Downloads**Documentation****System Description**

| | | |
|---|----------|----------|
| WAGO System Wiring, Selection Guide | pdf | Download |
| This guide will help you select the appropriate interface modules and system cables for the controller you are using. | 545.9 kB | |

Environmental Product Compliance**Compliance Search**

| | | |
|---|-----|----------|
| Environmental Product Compliance 706-2400/201-300 | URL | Download |
| System cable; for Siemens S7-400; 8 digital outputs for higher voltages; Length: 3 m; Conductor cross-section: 0.34 mm ² | | |

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.