





Dual P-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY

V _{DSS}	I _D	R _{DS(ON)} (m Ω) MAX
-20V	-5.3A	50 @ V _{GS} = -4.5V
		75 @ V _{GS} = -2.7V

FEATURES

- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- Surface Mount Package.



ABSOLUTE MAXIMUM RATINGS (T_A=25 °C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	-20	V
Gate-Source Voltage	V _{GS}	±12	V
Drain Current-Continuous ^a @ T _J =125 °C -Pulsed ^b (300us Pulse Width)	I _D	±5.3	A
	I _{DM}	±21	A
Drain-Source Diode Forward Current ^a	I _S	2.5	A
Maximum Power Dissipation ^a	P _D	2	W
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	R θ JA	62.5	°C/W
--	---------------	------	------

S DM4952

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D = -250uA	-20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -16V, V _{GS} =0V			-1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} = ±12V, V _{DS} =0V			±100	nA
ON CHARACTERISTICS ^b						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D = -250uA	-0.7			V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =-4.5V, I _D = -2.9A			50	m-ohm
		V _{GS} =-2.7V, I _D =-1.5A			75	m-ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = -5V, V _{GS} = -4.5V	-20			A
Forward Transconductance	g _{FS}	V _{DS} = -15V, I _D = - 4.9A		13		S
DYNAMIC CHARACTERISTICS ^c						
Input Capacitance	C _{ISS}	V _{DS} =-10V, V _{GS} = 0V f=1.0MHz		1190		pF
Output Capacitance	C _{OSS}			700		pF
Reverse Transfer Capacitance	C _{RSS}			250		pF
SWITCHING CHARACTERISTICS ^c						
Turn-On Delay Time	t _{D(ON)}	V _D = -10V, R _L =10 ohm I _D = -1A, V _{GEN} = -4.5V, R _{GEN} =6 ohm		19	40	ns
Rise Time	t _r			18	70	ns
Turn-Off Delay Time	t _{D(OFF)}			49	120	ns
Fall Time	t _f			28	130	ns
Total Gate Charge	Q _g	V _{DS} =-10V, I _D = - 1A, V _{GS} =-4.5V		20	25	nC
Gate-Source Charge	Q _{gs}			3.7		nC
Gate-Drain Charge	Q _{gd}			4.2		nC

S DM4952

ELECTRICAL CHARACTERISTICS (T_A=25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V _{SD}	V _{GS} = 0V, I _s = -1.7A		-0.87	-1.2	V

Notes

- a.Surface Mounted on FR4 Board, t<= 10sec.
- b.Pulse Test:Pulse Width<= 300us, Duty Cycle<= 2%.
- c.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature

SDM4952




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area

S DM4952




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms




Figure 13. Normalized Thermal Transient Impedance Curve