UF3X SERIES

SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER

产品规格确认书

Download from alldatasheet.com

UF3A THRU UF3M

SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER

康 比 電 子
HORNBY ELECTRONIC


REVERSE VOLTAGE: **50 to 1000 VOLTS**

FORWARD CURRENT: **3.0 AMPERE**

FEATURES

· Plastic package has Underwriters Laboratory Flammability Classification 94V-O
· For surface mounted applications
· Low profile package
· Easy pick and place
· Built-in strain relief
· Ultrafast recovery times for high efficiency
· High temperature soldering : 250°C /10 seconds at terminals

DO214-AB(SMC)



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case: Molded plastic, DO-214AB(SMC)
Terminals: Solder plated, solderable per MIL-STD-750, method 2026 guaranteed
Polarity: Color band denotes cathode end
Packaging: 16mm tape per EIA STD RS-481
Weight: 0.007 ounce, 0.21 gram

Maximum Ratings and Electrical Characteristics

Ratings at 25℃ ambient temperature unless otherwise specified.
Single phase, half wave, 60H_Z, resistive or inductive load.
For capacitive load, derate current by 20%.

	Symbols	*UF3A*	*UF3B*	*UF3D*	*UF3G*	*UF3J*	*UF3K*	*UF3M*	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	**Volts**
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	**Volts**
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	**Volts**
Maximum Average Forward Rectified Current at T_L=75℃	$I_{(AV)}$	3.0							**Amp**
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	100							**Amp**
Maximum Forward Voltage at 3.0A	V_F	1.0			1.3	1.7			**Volts**
Maximum Reverse Current at T_A=25℃ at Rated DC Blocking Voltage T_A=100℃	I_R	5.0 300							**μAmp**
Typical Junction Capacitance (Note 1)	C_J	75				63			**pF**
Typical Thermal Resistance (Note 2)	$R_{\theta JL}$	15							**℃/W**
Maximum Reverse Recovery Time (Note 3)	T_{RR}	50				75			**nS**
Operating Junction Temperature Range	T_J	-55 to +150							**℃**
Storage Temperature Range	Tstg	-55 to +150							**℃**

NOTES:

1- Measured at 1 MH_Z and applied reverse voltage of 4.0 VDC.

2- Thermal resistance from junction to lead mounted on P.C.B. with 0.3 x 0.3" (8.0 x 8.0mm) copper pad areas

3- Reverse Recovery Test Conditions：I_F=.5A，I_R=1A，I_{RR}=.25A.

Download from alldatasheet.com

UF3A THRU UF3M

SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER

康 比 電 子
HORNBY ELECTRONIC

RATINGS AND CHARACTERISTIC CURVES




Fig. 1-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




Fig. 2-MAXIMUM AVERAGE FORWARD CURRENT RATING




Fig. 3-TYPICAL REVERSE CHARACTERISTICS




Fig. 4-TYPICAL FORWARD CHARACTERISTICS




Fig. 5-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




Fig. 6-TYPICAL JUNCTION CAPACITANCE

Download from alldatasheet.com