

Feature

- Full diffusion process
- Capsule type ceramic package
- Double side cooling

Typical Application

- High power transmission
- Welding equipment
- Motor control and drive
- Battery charger

$I_{F(AV)}$	100A
V_{RRM}	100-5000V
I_{FSM}	8KA
I^2t	320 10 ³ a ² s

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (°C)	VALUE		UNIT
				Min	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Double side cooled, THS=97°C	150		100	A
V_{RRM}	Repetitive peak reverse voltage	$V_{DRM} \& V_{RRM} \text{ tp}=10\text{ms}$ $V_{DSM} \& V_{RSM} = V_{DRM} \& V_{RRM} + 100\text{V}$	150	100	5000	V
I_{RRM}	Repetitive peak current	$V_{RM} = V_{RRM}$	150		16	mA
I_{FSM}	Surge on-state current	10ms half sine wave $V_R = 0.6V_{RRM}$	150		8	KA
I^2t	I^2t for fusing coordination				320	A ² S*10
V_{FO}	Threshold voltage		150		0.80	V
r_T	On-state slop resistance				0.34	mΩ
V_{FM}	Peak on-state voltage	$I_{TM} = 314\text{A}, F = 15\text{KN}$	25		1.8	V
I_{RM}	Reverse recovery current	$I_{TM} = 314\text{A}, t_q = 1000\mu\text{s}$ $Di/dt = -20\text{A}/\mu\text{s}$ $V_r = 50\text{V}$	150		70	A
t_{rr}	Reverse recovery time				4.0	us
Q_{rr}	Recovery charge				140	uC
$R_{th(j-h)}$	Thermal resistance Junction to heat sink	At 180° sine double side cooled Clamping force 5.0kn			0.090	°C/W
F_M	Mounting force			3.5	5.5	KN
T_{stq}	Stored temperature			-40	200	°C
W_t	Weight					g
Outline						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7






Fig.8

Outline:



1



2