


Surface Mount VC-TCXO




ECVT45230

- Low Profile
- Low Current Consumption
- Excellent Stability
- 3V Supply
- Suitable for Reflow Soldering



Parameter	ECVT45230	
Frequency Range	12.80MHz to 19.68MHz	Specify
Temperature Stability	+/-2.5ppm -30 ⁰ to +80 ⁰ C	
Stability vs Supply	+/-0.3ppm	
Supply Voltage	+3V	
Supply Current	1.5mA	
Output Level	0.8V p-p (min)	
Output Waveform	Clipped Sine	
Output Load	10K Ω //10pF	
Start up time	3mS (max)	
Pulling Range	+/-7ppm to +/-12ppm	
Control Voltage	1.5 +/- 1.0V	
Phase Noise 100Hz offset	-110dBc / Hz (typ)	
1kHz offset	-130dBc / Hz (typ)	
Aging	+/-1ppm / yr	

Environmental & Mechanical	
Humidity	+40 ⁰ C +/-2 ⁰ C 90% RH for 200Hours
Thermal Shock	+85 ⁰ C for 30 mins -30 ⁰ C for 30 mins
Vibration	10 - 55Hz 2mm amplitude 2 hours XYZ axis
Soldering Condition	235 +/-5 ⁰ c 2 Seconds +/-0.5 S



Part Numbering ECVT45230 Z 19.20M
Type _____

Z= Clipped Sine _____

Frequency _____

Type	A	B	C	D	E	F	G
All	7.0	5.0	1.8	5.08	1.0	3.0	1.4

Dimensions inmm

Pin	1	2	3	4	5	6	7	8
	VCont	GND	N/C	N/C	O/P	Vcc	N/C	N/C

ECM Electronics Limited, Penmaen House, Ashington, West Sussex, RH20 3JR, UK
Tel: +44(0)1903 892810: Fax: +44(0)1903 892738. Email: ecm@ecmelectronics.co.uk

Although we have attempted to accurately reflect the products we market. ECM reserve the right without prior notice to discontinue any product or make design changes we believe necessary. Issue 2