TRIAC(Surface Mount Device / Non-isolated)

TMG3C80D

SanRex Triac **TMG3C80D** is designed for full wave AC control applications. It can be used as an ON/OFF function or for phase control operation.


Typical Applications

- Home Appliances : Washing Machines, Vacuum Cleaners, Rice Cookers, Micro Wave Ovens, Hair Dryers, other control applications
- Industrial Use : SMPS, Copier Machines, Motor Controls, Dimmer, SSR, Heater Controls, Vending Machines, other control applications

Features

- $I_{T(RMS)}$=3A
- High Surge Current
- Low Voltage Drop
- Lead-Free Package

TO-252



Identifying Code : T3C8D Unit : mm

■Maximum Ratings


(Tj=25℃ unless otherwise specified)

Symbol	Item	Reference	Ratings	Unit
V_{DRM}	Repetitive Peak Off-State Voltage		800	V
$I_{T(RMS)}$	R.M.S. On-State Current	Tc=111℃	3	A
I_{TSM}	Surge On-State Current	One cycle, 50Hz/60Hz, Peak value non-repetitive	27/30	A
I^2t	I^2t (for fusing)		3.7	A^2S
P_{GM}	Peak Gate Power Dissipation		1.5	W
$P_{G(AV)}$	Average Gate Power Dissipation		0.1	W
I_{GM}	Peak Gate Current		1	A
V_{GM}	Peak Gate Voltage		7	V
Tj	Operating Junction Temperature		−40～+125	℃
Tstg	Storage Temperature		−40～+150	℃
	Mass		0.32	g

■Electrical Characteristics


Symbol		Item	Reference	Ratings			Unit
				Min.	Typ.	Max.	
I_{DRM}		Repetitive Peak Off-State Current	$V_D=V_{DRM}$, Single phase, half wave, Tj=125℃			1	mA
V_{TM}		Peak On-State Voltage	I_T=4.5A, Inst. measurement			1.4	V
I_{GT1}^{+}	1	Gate Trigger Current	V_D=6V, R_L=10Ω			15	mA
I_{GT1}^{-}	2					15	
I_{GT3}^{+}	3					—	
I_{GT3}^{-}	4					15	
V_{GT1}^{+}	1	Gate Trigger Voltage				1.5	V
V_{GT1}^{-}	2					1.5	
V_{GT3}^{+}	3					—	
V_{GT3}^{-}	4					1.5	
V_{GD}		Non-Trigger Gate Voltage	Tj=125℃, $V_D=\frac{1}{2}V_{DRM}$	0.2			V
〔dv/dt〕c		Critical Rate of Rise of Off-State Voltage at Commutation	Tj=125℃, 〔di/dt〕c=−1.5A/ms, V_D=400V	5			V/μs
I_H		Holding Current			2		mA
Rth(j-c)		Thermal Resistance	Junction to case			3.8	℃/W
Rth(j-a)			Junction to ambient			60	

Trigger mode of the triac




SanRex 50 Seaview Blvd. Port Washington, NY 11050 PH(516)625-1313 FX(516)625-8845 E-mail:semi@sanrex.com


Gate Characteristics




On-State Characteristics (MAX)




RMS On-State Current vs Maximum Power Dissipation




RMS On-State vs Allowable Case Temperature




Surge On-State Current Rating (Non-Repetitive)




Transient Thermal Impedance



IGT −Tj (Typical)



VGT −Tj (Typical)



RMS On-State vs
Allowable Ambient Temperature

