

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0039013123](#)
Status: **Active**
Overview: [minifit_jr](#)
Description: 4.20mm (.165") Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 12 Circuits

Documents:

[3D Model](#) [Product Specification PS-5556-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	Crimp Housings
Series	5559
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.
MolexKits	Yes
Overview	minifit_jr
Product Name	Mini-Fit Jr.™

Physical

Breakaway	No
Circuits (maximum)	12
Color - Resin	Natural
Flammability	94V-2
Gender	Male
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.165 In
Pitch - Mating Interface (mm)	4.20 mm
Pitch - Term. Interface (in)	0.165 In
Pitch - Term. Interface (mm)	4.20 mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Electrical

Current - Maximum per Contact	13A
-------------------------------	-----

Material Info

Old Part Number	5559-12P1
-----------------	-----------

Reference - Drawing Numbers

Packaging Specification	PK-5559-002
Product Specification	PS-5556-001




image - Reference only

Series

EU RoHS

**ELV and RoHS
Compliant**
REACH SVHC
Contains SVHC: No
Halogen-Free
Status

Not Reviewed

**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

China RoHS







Search Parts in this Series
[5559Series](#)

Mates With
[5557](#) Receptacle Housing


Use With
[41995](#) Strain Relief

This document was generated on 06/08/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



CKT. SIZE	DIM. A	DIM. B
6	.331 (8.40)	.543 (13.80)
8	.496 (12.60)	.709 (18.00)
10	.661 (16.80)	.874 (22.20)
12	.827 (21.00)	1.039 (26.40)
14	.992 (25.20)	1.205 (30.60)
16	1.157 (29.40)	1.370 (34.80)
18	1.323 (33.60)	1.535 (39.00)
20	1.488 (37.80)	1.701 (43.20)
22	1.654 (42.00)	1.866 (47.40)
24	1.819 (46.20)	2.031 (51.60)



- NOTES:
- MATERIAL: BLANK=NYLON 6/6, UL 94V-2, COLOR: NATURAL
BL=NYLON 6/6, UL94V-2, COLOR: BLACK
210=NYLON 6/6, UL 94V-0, COLOR: NATURAL
220=NYLON 6/6, UL 94V-2, U.V. STABILIZED, COLOR: BLACK
 - FINISH: N/A
 - PRODUCT SPECIFICATION: PS-5556-001
 - PACKAGING SPECIFICATION: SEE CHARTS
 - THIS PART MATES WITH RECEPTACLE #5557
 - THIS PART IS FOR USE WITH MOLEX MALE TERMINAL #5558-*

ADDED PK SPECS EC NO: UCP2009-0724 DRWN:JKLOSTENIER 2008/10/01 CHKD:JBELL 2008/10/03 APPR:FSMITH 2008/10/03	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		mm		INCH		DRAWN BY RJF		DATE 1989/09/22	
		4 PLACES ± --- ± ---		3 PLACES ± --- ± .015		CHECKED BY BAP		DATE 1989/09/22	
		2 PLACES ± 0.38 ± ---		1 PLACE ± --- ± ---		APPROVED BY ROS		DATE 1989/09/22	
ANGULAR ± 1/2°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		DOCUMENT NO. SD-5559-NP1*		SHEET NO. 1 OF 2	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

	13	12	11	10	9	8	7	6	5	4	3	2	1	
	PART NUMBER	ENG. NUMBER	CIRCUIT SIZE	MATERIAL	PACKAGING SPECIFICATION	PART NUMBER	ENG. NUMBER	CIRCUIT SIZE	MATERIAL	PACKAGING SPECIFICATION	<div>LEGEND</div> <div> <div>5559-**-PI-*</div> <div>BASE NO</div> <div>CIRCUIT SIZE (02-24)</div> <div>PLUG WITHOUT MOUNTING EARS</div> </div> <div>MATERIAL OPTION: (SEE NOTE 1 ON SHEET 1.)</div>			
J	39-01-3023	5559-02P I	2	94V-2	PK-5559-002	39-01-3029	5559-02P I-2 I O	2	94V-0	PK-5559-002				J
	39-01-3043	5559-04P I	4	94V-2	BULK	39-01-3049	5559-04P I-2 I O	4	94V-0	BULK				
	39-01-3063	5559-06P I	6	94V-2	BULK	39-01-3069	5559-06P I-2 I O	6	94V-0	BULK				
I	39-01-3083	5559-08P I	8	94V-2	BULK	39-01-3089	5559-08P I-2 I O	8	94V-0	BULK				I
	39-01-3103	5559-10P I	10	94V-2	BULK	39-01-3109	5559-10P I-2 I O	10	94V-0	BULK				
	39-01-3123	5559-12P I	12	94V-2	BULK	39-01-3129	5559-12P I-2 I O	12	94V-0	BULK				
H	39-01-3143	5559-14P I	14	94V-2	BULK	39-01-3149	5559-14P I-2 I O	14	94V-0	BULK				H
	39-01-3163	5559-16P I	16	94V-2	BULK	39-01-3169	5559-16P I-2 I O	16	94V-0	BULK				
	39-01-3183	5559-18P I	18	94V-2	BULK	39-01-3189	5559-18P I-2 I O	18	94V-0	BULK				
G	39-01-3203	5559-20P I	20	94V-2	BULK	39-01-3209	5559-20P I-2 I O	20	94V-0	BULK				G
	39-01-3223	5559-22P I	22	94V-2	BULK	39-01-3229	5559-22P I-2 I O	22	94V-0	BULK				
	39-01-3243	5559-24P I	24	94V-2	BULK	39-01-3249	5559-24P I-2 I O	24	94V-0	BULK				
F														F
	PART NUMBER	ENG. NUMBER	CIRCUIT SIZE	MATERIAL	PACKAGING SPECIFICATION	PART NUMBER	ENG. NUMBER	CIRCUIT SIZE	MATERIAL	PACKAGING SPECIFICATION				
E	I5-04-6020	5559-02P I-220	2	94V-2, U.V. STABILIZED	PK-5559-002	39-01-3026	5559-02P1-BL	2	94V-2	PK-5559-002				E
	NO E.D.P.	5559-04P I-220	4	94V-2, U.V. STABILIZED	BULK	39-01-3046	5559-04P1-BL	4	94V-2	BULK				
	NO E.D.P.	5559-06P I-220	6	94V-2, U.V. STABILIZED	BULK	39-01-3066	5559-06P1-BL	6	94V-2	BULK				
	NO E.D.P.	5559-08P I-220	8	94V-2, U.V. STABILIZED	BULK	39-01-3086	5559-08P1-BL	8	94V-2	BULK				
D	NO E.D.P.	5559-10P I-220	10	94V-2, U.V. STABILIZED	BULK	39-01-3106	5559-10P1-BL	10	94V-2	BULK				D
	NO E.D.P.	5559-12P I-220	12	94V-2, U.V. STABILIZED	BULK	39-01-3126	5559-12P1-BL	12	94V-2	BULK				
	NO E.D.P.	5559-14P I-220	14	94V-2, U.V. STABILIZED	BULK	39-01-3146	5559-14P1-BL	14	94V-2	BULK				
C	NO E.D.P.	5559-16P I-220	16	94V-2, U.V. STABILIZED	BULK	39-01-3166	5559-16P1-BL	16	94V-2	BULK				C
	NO E.D.P.	5559-18P I-220	18	94V-2, U.V. STABILIZED	BULK									
	NO E.D.P.	5559-20P I-220	20	94V-2, U.V. STABILIZED	BULK									
B	NO E.D.P.	5559-22P I-220	22	94V-2, U.V. STABILIZED	BULK									B
	NO E.D.P.	5559-24P I-220	24	94V-2, U.V. STABILIZED	BULK									
A														A