


MIL-C-11015 & 39014 Multilayer Ceramic Capacitors

CK and CKR Military Grade Capacitors



MIL-C-11015 & 39014 - CK and CKR - military grade capacitors are available as radial and axial leaded capacitors with the option of hot solder dipped leads on the CKRs.


Highlights

- Available on tape and reel
- Molded case construction
- CKR available with stand-off
- Hot solder dip leads on Type CKR

Specifications

Capacitance Range: 10 pF to 3.3 μ F
Voltage Range: 50, 100, 200 Vdc
Temperature Coefficient: X7R (Mil BX or BR)

Outline Drawings



Radial

Type	Inches					mm				
	L	H	T	S	d	L	H	T	S	d
CK05	.190	.190	.090	.200	.025	4.8	4.8	2.3	5.1	.64
CKR05	.190	.190	.090	.200	.025	4.8	4.8	2.3	5.1	.64
CK06	.290	.290	.090	.200	.025	7.4	7.4	2.3	5.1	.64
CKR06	.290	.290	.090	.200	.025	7.4	7.4	2.3	5.1	.64

Axial

Type	Inches			mm		
	D	L	d	D	L	d
CK12	.090	.160	.020	2.3	4.0	.51
CKR11	.090	.160	.020	2.3	4.0	.51
CK13	.090	.250	.020	2.3	6.4	.51
CKR12	.090	.250	.020	2.3	6.4	.51
CK14	.140	.390	.025	3.6	9.9	.64
CKR14	.140	.390	.025	3.6	9.9	.64
CK15	.250	.500	.025	6.4	12.7	.64
CKR15	.250	.500	.025	6.4	12.7	.64
CK16	.350	.690	.025	8.9	17.5	.64
CKR16	.350	.690	.025	8.9	17.5	.64

TO ORDER MIL-C-11015 PARTS:

Order by CK part number shown in Ratings Table
Example: CK05BX104M

TO ORDER MIL-C-39014 PARTS:

Indicate the prefix M39014/-- followed by the applicable MIL dash number. Example: For M39014/01-1594 (CKR05BX104MS); order M39014/011594

MIL-C-11015 & 39014 Multilayer Ceramic Capacitors

Ratings

Cap	Tol. %	MIL-C-11015/18	MIL-C-39014/01	39014/01 Failure Rate Levels			
			References	M	P	R	S
50 Vdc - Radial Leaded - CK05/M39014/01							
			CKR05BX123K*	1457	1497	1537	1577
			CKR05BX153K*	1458	1498	1538	1578
			CKR05BX153M*	1459	1499	1539	1579
			CKR05BX183K*	1460	1500	1540	1580
			CKR05BX223K*	1461	1501	1541	1581
			CKR05BX223M*	1462	1502	1542	1582
			CKR05BX273K*	1463	1503	1543	1583
			CKR05BX333K*	1464	1504	1544	1584
			CKR05BX333M*	1465	1505	1545	1585
			CKR05BX393K*	1466	1506	1546	1586
			CKR05BX473K*	1467	1507	1547	1587
			CKR05BX473M*	1468	1508	1548	1588
			CKR05BX563K*	1469	1509	1549	1589
			CKR05BX683K*	1470	1510	1550	1590
			CKR05BX683M*	1471	1511	1551	1591
			CKR05BX823K*	1472	1512	1552	1592
			CKR05BX104K*	1473	1513	1553	1593
			CKR05BX104M*	1474	1514	1554	1594
100 Vdc - Radial Leaded - CK05/M39014/01							
			CKR05BX122K*	1239	1279	1319	1359
			CKR05BX152K*	1240	1280	1320	1360
			CKR05BX152M*	1441	1481	1521	1561
			CKR05BX182K*	1442	1482	1522	1562
			CKR05BX222K*	1443	1483	1523	1563
			CKR05BX222M*	1444	1484	1524	1564
			CKR05BX272K*	1445	1485	1525	1565
			CKR05BX332K*	1446	1486	1526	1566
			CKR05BX332M*	1447	1487	1527	1567
			CKR05BX392K*	1448	1488	1528	1568
			CKR05BX472K*	1449	1489	1529	1569
			CKR05BX472M*	1450	1490	1530	1570
			CKR05BX562K*	1451	1491	1531	1571
			CKR05BX682K*	1452	1492	1532	1572
			CKR05BX682M*	1453	1493	1533	1573
			CKR05BX822K*	1454	1494	1534	1574
			CKR05BX103K*	1455	1495	1535	1575
			CKR05BX103M*	1456	1496	1536	1576

Cap	Tol.	MIL-C-11015/18	MIL-C-39014/01	39014/01 Failure Rate Levels			
	%		References	M	P	R	S
200 Vdc - Radial Leaded - CK05/M39014/01							
			CKR05BX100K*	1201	1241	1281	1321
			CKR05BX100M*	1202	1242	1282	1322
			CKR05BX120K*	1203	1243	1283	1323
			CKR05BX150K*	1204	1244	1284	1324
			CKR05BX150M*	1205	1245	1285	1325
			CKR05BX180K*	1206	1246	1286	1326
			CKR05BX220K*	1207	1247	1287	1327
			CKR05BX220M*	1208	1248	1288	1328
			CKR05BX270K*	1209	1249	1289	1329
			CKR05BX330K*	1210	1250	1290	1330
			CKR05BX330M*	1211	1251	1291	1331
			CKR05BX390K*	1212	1252	1292	1332
			CKR05BX470K*	1213	1253	1293	1333
			CKR05BX470M*	1214	1254	1294	1334
			CKR05BX560K*	1215	1255	1295	1335
			CKR05BX680K*	1216	1256	1296	1336
			CKR05BX680M*	1217	1257	1297	1337
			CKR05BX820K*	1218	1258	1298	1338
			CKR05BX101K*	1219	1259	1299	1339
			CKR05BX101M*	1220	1260	1300	1340
			CKR05BX121K*	1221	1261	1301	1341
			CKR05BX151K*	1222	1262	1302	1342
			CKR05BX151M*	1223	1263	1303	1343
			CKR05BX181K*	1224	1264	1304	1344
			CKR05BX221K*	1225	1265	1305	1345
			CKR05BX221M*	1226	1266	1306	1346
			CKR05BX271K*	1227	1267	1307	1347
			CKR05BX331K*	1228	1268	1308	1348
			CKR05BX331M*	1229	1269	1309	1349
			CKR05BX391K*	1230	1270	1310	1350
			CKR05BX471K*	1231	1271	1311	1351
			CKR05BX471M*	1232	1272	1312	1352
			CKR05BX561K*	1233	1273	1313	1353
			CKR05BX681K*	1234	1274	1314	1354
			CKR05BX681M*	1235	1275	1315	1355
			CKR05BX821K*	1236	1276	1316	1356
			CKR05BX102K*	1237	1277	1317	1357
			CKR05BX102M*	1238	1278	1318	1358

*Insert proper letter symbol for Failure Rate Designator

M = 1% / 1000 Hours, P = 0.1% / 1000 Hours

R = 0.01% / 1000 Hours, S = 0.001% / 1000 Hours

Add 'V' at end of failure rate designator if stand-off design is required, (CKR only)

Add 'TR' to end of part number for Tape & Reel

Leads will be trimmed to .625" length

CK05 - 2,000 per reel

CKR05 - 1,700 per reel

(Available in full reels only)

MIL-C-11015 & 39014 Multilayer Ceramic Capacitors

Ratings

Cap	Tol. %	MIL-C-11015/19	MIL-C-39014/02	39014/02 Failure Rate Levels					
			References	M	P	R	S		
50 Vdc - Radial Leaded - CK06/M39014/02									
			CKR06BX124K*	1233	1273	1313	1353		
			CKR06BX154K*	1234	1274	1314	1354		
			CKR06BX184K*	1235	1275	1315	1355		
			CKR06BX224K*	1236	1276	1316	1356		
			CKR06BX274K*	1237	1277	1317	1357		
			CKR06BX334K*	1238	1278	1318	1358		
			CKR06BX394K*	1239	1279	1319	1359		
			CKR06BX474K*	1240	1280	1320	1360		
			CKR06BX564K*	1404	1408	1412	1416		
			CKR06BX684K*	1405	1409	1413	1417		
			CKR06BX824K*	1406	1410	1414	1418		
			CKR06BX105K*	1407	1411	1415	1419		
			100 Vdc - Radial Leaded - CK06/M39014/02						
						CKR06BX123K*	1231	1271	1311
CKR06BX153K*	1220	1260				1300	1340		
CKR06BX183K*	1221	1261				1301	1341		
CKR06BX223K*	1222	1262				1302	1342		
CKR06BX273K*	1232	1272				1312	1352		
CKR06BX333K*	1223	1263				1303	1343		
CKR06BX393K*	1224	1264				1304	1344		

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/02	39014/02 Failure Rate Levels			
	%		References	M	P	R	S
100 Vdc - Radial Leaded - CK05/M39014/02							
			CKR06BX473K*	1225	1265	1305	1345
			CKR06BX563K*	1226	1266	1306	1346
			CKR06BX683K*	1227	1267	1307	1347
			CKR06BX823K*	1228	1268	1308	1348
			CKR06BX104K*	1229	1269	1309	1349
200 Vdc - Radial Leaded - CK06/M39014/02							
			CKR06BX122K*	1201	1241	1281	1321
			CKR06BX152K*	1202	1242	1282	1322
			CKR06BX152M*	1203	1243	1283	1323
			CKR06BX182K*	1204	1244	1284	1324
			CKR06BX222K*	1206	1246	1286	1326
			CKR06BX222M*	1207	1247	1287	1327
			CKR06BX272K*	1208	1248	1288	1328
			CKR06BX332K*	1209	1249	1289	1329
			CKR06BX332M*	1210	1250	1290	1330
			CKR06BX392K*	1211	1251	1291	1331
			CKR06BX472K*	1212	1252	1292	1332
			CKR06BX472M*	1213	1253	1293	1333
			CKR06BX562K*	1214	1254	1294	1334
			CKR06BX682K*	1215	1255	1295	1335
			CKR06BX682M*	1216	1256	1296	1336
			CKR06BX822K*	1217	1257	1297	1337
			CKR06BX103K*	1218	1258	1298	1338
			CKR06BX103M*	1219	1259	1299	1339

Add 'TR' to end of part number for Tape & Reel
Leads will be trimmed to .625" length
CK06 & CKR06 1,500 per reel
(Available in full reels only)

*Insert proper letter symbol for Failure Rate Designator
M = 1% / 1000 Hours, P = 0.1% / 1000 Hours
R = 0.01% / 1000 Hours, S = 0.001% / 1000 Hours
Add 'V' at end of failure rate designator if stand-off design is required, (CKR only)

Cap	Tol. %	MIL-C-11015/20	MIL-C-39014/05 References	39014/05 Failure Rate Levels			
				M	P	R	S
50 Vdc - Axial Leaded - CK12/M39014/05							
6600 pF	10	CK12BX562K	CKR11BX562K*	2651	2851	2051	2251
6800 pF	10	CK12BX682K	CKR11BX682K*	2652	2852	2052	2252
6800 pF	20	CK12BX682M	CKR11BX682M*	2653	2853	2053	2253
8200 pF	10	CK12BX822K	CKR11BX822K*	2654	2854	2054	2254
0.01 uF	10	CK12BX103K	CKR11BX103K*	2655	2855	2055	2255
0.01 uF	20	CK12BX103M	CKR11BX103M*	2656	2856	2056	2256

Cap	Tol.	MIL-C-11015/20	MIL-C-39014/05	39014/05 Failure Rate Levels			
	%		References	M	P	R	S
100 Vdc - Axial Leaded - CK12/M39014/05							
10 pF	10	CK12BX100K	CKR11BX100K*	2601	2801	2001	2201
10 pF	20	CK12BX100M	CKR11BX100M*	2602	2802	2002	2202
12 pF	10	CK12BX120K	CKR11BX120K*	2603	2803	2003	2203
15 pF	10	CK12BX150K	CKR11BX150K*	2604	2804	2004	2204
15 pF	20	CK12BX150M	CKR11BX150M*	2605	2805	2005	2205
18 pF	10	CK12BX180K	CKR11BX180K*	2606	2806	2006	2206

MIL-C-11015 & 39014 Multilayer Ceramic Capacitors

Ratings

Cap	Tol.	MIL-C-11015/20	MIL-C-39014/05 References	39014/05 Failure Rate Levels			
	%			M	P	R	S
100 Vdc - Axial Leaded - CK12/M39014/05							
22 pF	10	CK12BX220K	CKR11BX220K*	2607	2807	2007	2207
22 pF	20	CK12BX220M	CKR11BX220M*	2608	2808	2008	2208
27 pF	10	CK12BX270K	CKR11BX270K*	2609	2809	2009	2209
33 pF	10	CK12BX330K	CKR11BX330K*	2610	2810	2010	2210
33 pF	20	CK12BX330M	CKR11BX330M*	2611	2811	2011	2211
39 pF	10	CK12BX390K	CKR11BX390K*	2612	2812	2012	2212
47 pF	10	CK12BX470K	CKR11BX470K*	2613	2813	2013	2213
47 pF	20	CK12BX470M	CKR11BX470M*	2614	2814	2014	2214
56 pF	10	CK12BX560K	CKR11BX560K*	2615	2815	2015	2215
68 pF	10	CK12BX680K	CKR11BX680K*	2616	2816	2016	2216
68 pF	20	CK12BX680M	CKR11BX680M*	2617	2817	2017	2217
82 pF	10	CK12BX820K	CKR11BX820K*	2618	2818	2018	2218
100 pF	10	CK12BX101K	CKR11BX101K*	2619	2819	2019	2219
100 pF	20	CK12BX101M	CKR11BX101M*	2620	2820	2020	2220
120 pF	10	CK12BX121K	CKR11BX121K*	2621	2821	2021	2221
150 pF	10	CK12BX151K	CKR11BX151K*	2622	2822	2022	2222
150 pF	20	CK12BX151M	CKR11BX151M*	2623	2823	2023	2223
180 pF	10	CK12BX181K	CKR11BX181K*	2624	2824	2024	2224
220 pF	10	CK12BX221K	CKR11BX221K*	2625	2825	2025	2225
220 pF	20	CK12BX221M	CKR11BX221M*	2626	2826	2026	2226
270 pF	10	CK12BX271K	CKR11BX271K*	2627	2827	2027	2227
330 pF	10	CK12BX331K	CKR11BX331K*	2628	2828	2028	2228

*Insert proper letter symbol for Failure Rate Designator
M = 1% / 1000 Hours, P = 0.1% / 1000 Hours
R = 0.01% / 1000 Hours, S = 0.001% / 1000 Hours

Cap	Tol.	MIL-C-11015/20	MIL-C-39014/05 References	39014/05 Failure Rate Levels			
	%			M	P	R	S
100 Vdc - Axial Leaded - CK12/M39014/05							
330 pF	20	CK12BX331M	CKR11BX331M*	2629	2829	2029	2229
390 pF	10	CK12BX391K	CKR11BX391K*	2630	2830	2030	2230
470 pF	10	CK12BX471K	CKR11BX471K*	2631	2831	2031	2231
470 pF	20	CK12BX471M	CKR11BX471M*	2632	2832	2032	2232
560 pF	10	CK12BX561K	CKR11BX561K*	2633	2833	2033	2233
680 pF	10	CK12BX681K	CKR11BX681K*	2634	2834	2034	2234
680 pF	20	CK12BX681M	CKR11BX681M*	2635	2835	2035	2235
820 pF	10	CK12BX821K	CKR11BX821K*	2636	2836	2036	2236
1000 pF	10	CK12BX102K	CKR11BX102K*	2637	2837	2037	2237
1000 pF	20	CK12BX102M	CKR11BX102M*	2638	2838	2038	2238
1200 pF	10	CK12BX122K	CKR11BX122K*	2639	2839	2039	2239
1500 pF	10	CK12BX152K	CKR11BX152K*	2640	2840	2040	2240
1500 pF	20	CK12BX152M	CKR11BX152M*	2641	2841	2041	2241
1800 pF	10	CK12BX182K	CKR11BX182K*	2642	2842	2042	2242
2200 pF	10	CK12BX222K	CKR11BX222K*	2643	2843	2043	2243
2200 pF	20	CK12BX222M	CKR11BX222M*	2644	2844	2044	2244
2700 pF	10	CK12BX272K	CKR11BX272K*	2645	2845	2045	2245
3300 pF	10	CK12BX332K	CKR11BX332K*	2646	2846	2046	2246
3300 pF	20	CK12BX332M	CKR11BX332M*	2647	2847	2047	2247
3900 pF	10	CK12BX392K	CKR11BX392K*	2648	2848	2048	2248
4700 pF	10	CK12BX472K	CKR11BX472K*	2649	2849	2049	2249
4700 pF	20	CK12BX472M	CKR11BX472M*	2650	1850	2050	2250

Add 'TR' to end of part number for Tape & Reel
CK12 & CKR11 5,000 per reel
(Available in full reels only)

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05 References	39014/05 Failure Rate Levels			
	%			M	P	R	S
50 Vdc - Axial Leaded - CK13/M39014/05							
.012 uF	10	CK13BX123K	CKR12BX123K*	2663	2863	2063	2263
.015 uF	10	CK13BX153K	CKR12BX153K*	2664	2864	2064	2264
.015 uF	20	CK13BX153M	CKR12BX153M*	2665	2865	2065	2265
.018 uF	10	CK13BX183K	CKR12BX183K*	2666	2866	2066	2266
.022 uF	10	CK13BX223K	CKR12BX223K*	2667	2867	2067	2267
.022 uF	20	CK13BX223M	CKR12BX223M*	2668	2868	2068	2268
.027 uF	10	CK13BR273K	CKR12BX273K*	2669	2869	2069	2269
.033 uF	10	CK13BR333K	CKR12BX333K*	2670	2870	2070	2270
.033 uF	20	CK13BR333M	CKR12BX333M*	2671	2871	2071	2271

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05 References	39014/05 Failure Rate Levels			
	%			M	P	R	S
50 Vdc - Axial Leaded - CK13/M39014/05							
.039 uF	10	CK13BR393K	CKR12BX393K*	2672	2872	2072	2272
.047 uF	10	CK13BR473K	CKR12BX473K*	2673	2873	2073	2273
.047 uF	20	CK13BR473M	CKR12BX473M*	2674	2874	2074	2274
100 Vdc - Axial Leaded - CK13/M39014/05							
5600 pF	10	CK13BX562K	CKR12BX562K*	2657	2857	2057	2257
6800 pF	10	CK13BX682K	CKR12BX682K*	2658	2858	2058	2258
6800 pF	20	CK13BX682M	CKR12BX682M*	2659	2859	2059	2259
8200 pF	10	CK13BX822K	CKR12BX822K*	2660	2860	2060	2260
.01 uF	10	CK13BX103K	CKR12BX103K*	2661	2861	2061	2261
.01 uF	20	CK13BX103M	CKR12BX103M*	2662	2862	2062	2262

MIL-C-11015 & 39014 Multilayer Ceramic Capacitors

Ratings

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels				Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels			
Cap	%		References	M	P	R	S	Cap	%		References	M	P	R	S
50 Vdc - Axial Leaded - CK14/M39014/05								100 Vdc - Axial Leaded - CK14/M39014/05							
.056 uF	10		CKR14BX563K*	2687	2887	2087	2287	.015 uF	20	CK14BX153M	CKR14BX153M*	2677	2877	2077	2277
.068 uF	10		CKR14BX683K*	2688	2888	2088	2288	.018 uF	10	CK14BX183K	CKR14BX183K*	2678	2878	2078	2278
.068 uF	20		CKR14BX683M*	2689	2889	2089	2289	.022 uF	10	CK14BX223K	CKR14BX223K*	2679	2879	2079	2279
.082 uF	10		CKR14BX823K*	2690	2890	2090	2290	.022 uF	20	CK14BX223M	CKR14BX223M*	2680	2880	2080	2280
.10 uF	10		CKR14BX104K*	2691	2891	2091	2291	.027 uF	10	CK14BX273K	CKR14BX273K*	2681	2881	2081	2281
.10 uF	20		CKR14BX104M*	2692	2892	2092	2292	.033 uF	10	CK14BX333K	CKR14BX333K*	2682	2882	2082	2282
.12 uF	10	CK14BR124K	CKR14BR124K*	2699	2899	2099	2299	.033 uF	20	CK14BX333M	CKR14BX333M*	2683	2883	2083	2283
.15 uF	10	CK14BR154K	CKR14BR154K*	2700	2900	2100	2300	.039 uF	10	CK14BX393K	CKR14BX393K*	2684	2884	2084	2284
.15 uF	20	CK14BR154M	CKR14BR154M*	2701	2901	2101	2301	.047 uF	10	CK14BX473K	CKR14BX473K*	2685	2885	2085	2285
.18 uF	10	CK14BR184K	CKR14BR184K*	2702	2902	2102	2302	.047 uF	20	CK14BX473M	CKR14BX473M*	2686	2886	2086	2286
.22 uF	10	CK14BR224K	CKR14BR224K*	2703	2903	2103	2303	.056 uF	10	CK14BR563K	CKR14BR563K*	2693	2893	2093	2293
.22 uF	20	CK14BR224M	CKR14BR224M*	2704	2904	2104	2304	.068 uF	10	CK14BR683K	CKR14BR683K*	2694	2894	2094	2294
.27 uF	10	CK14BR274K	CKR14BR274K*	2705	2905	2105	2305	.068 uF	20	CK14BR683M	CKR14BR683M*	2695	2895	2095	2295
100 Vdc - Axial Leaded - CK14/M39014/05								.082 uF	10	CK14BR823K	CKR14BR823K*	2696	2896	2096	2296
.012 uF	10	CK14BX123K	CKR14BX123K*	2675	2875	2075	2275	.1 uF	10	CK14BR104K	CKR14BR104K*	2697	2897	2097	2297
.015 uF	10	CK14BX153K	CKR14BX153K*	2676	2876	2076	2276	.1 uF	20	CK14BR104M	CKR14BR104M*	2698	2898	2098	2298

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels				Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels			
Cap	%		References	M	P	R	S	Cap	%		References	M	P	R	S
50 Vdc - Axial Leaded - CK15/M39014/05								100 Vdc - Axial Leaded - CK15/M39014/05							
.33 uF	10	CK15BR334K	CKR15BR334K*	2719	2919	2119	2319	.068 uF	20		CKR15BX683M*	2708	2908	2108	2308
.33 uF	20	CK15BR334M	CKR15BR334M*	2720	2920	2120	2320	.082 uF	10		CKR15BX823K*	2709	2909	2109	2309
.47 uF	10	CK15BR474K	CKR15BR474K*	2721	2921	2121	2321	.10 uF	10	CK15BX104K	CKR15BX104K*	2710	2910	2110	2310
.47 uF	20	CK15BR474M	CKR15BR474M*	2722	2922	2122	2322	.10 uF	20	CK15BX104M	CKR15BX104M*	2711	2911	2111	2311
.68 uF	10		CKR15BR684K*	2723	2923	2123	2323	.12 uF	10	CK15BR124K	CKR15BR124K*	2712	2912	2112	2312
.68 uF	20		CKR15BR684M*	2724	2924	2124	2324	.15 uF	10	CK15BR154K	CKR15BR154K*	2713	2913	2113	2313
1.0 uF	10	CK15BR105K	CKR15BR105K*	2725	2925	2125	2325	.15 uF	20	CK15BR154M	CKR15BR154M*	2714	2914	2114	2314
1.0 uF	20	CK15BR105M	CKR15BR105M*	2726	2926	2126	2326	.18 uF	10	CK15BR184K	CKR15BR184K*	2715	2915	2115	2315
100 Vdc - Axial Leaded - CK15/M39014/05								.22 uF	10	CK15BR224K	CKR15BR224K*	2716	2916	2116	2316
.056 uF	10		CKR15BX563K*	2706	2906	2106	2306	.22 uF	20	CK15BR224M	CKR15BR224M*	2717	2917	2117	2317
.068 uF	10		CKR15BX683K*	2707	2907	2107	2307	.27 uF	10	CK15BR274K	CKR15BR274K*	2718	2918	2118	2318

Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels				Cap	Tol.	MIL-C-11015/19	MIL-C-39014/05	39014/05 Failure Rate Levels			
Cap	%		References	M	P	R	S	Cap	%		References	M	P	R	S
50 Vdc - Axial Leaded - CK16/M39014/05								100 Vdc - Axial Leaded - CK16/M39014/05							
10 uF	10	CK16BR105K	CKR16BR105K*	2731	2931	2131	2331	.47 uF	10	CK16BR474K	CKR16BR474K*	2727	2927	2127	2327
10 uF	20	CK16BR105M	CKR16BR105M*	2732	2932	2132	2332	.47 uF	20	CK16BR474M	CKR16BR474M*	2728	2928	2128	2328
2.2 uF	10	CK16BR225K	CKR16BR225K*	2733	2933	2133	2333	.68 uF	10		CKR16BR684K*	2729	2929	2129	2329
2.2 uF	20	CK16BR225M	CKR16BR225M*	2734	2934	2134	2334	.68 uF	20		CKR16BR684M*	2730	2930	2130	2330
.3 uF	10	CK16BR335K	CKR16BR335K*	2735	2935	2135	2335								
3.3 uF	20	CK16BR335M	CKR16BR335M*	2736	2936	2136	2336								

*Insert proper letter symbol for Failure Rate Designator
M = 1% / 1000 Hours, P = 0.1% / 1000 Hours
R = 0.01% / 1000 Hours, S = 0.001% / 1000 Hours
Add 'V' at end of failure rate designator if stand-off design is required, (CKR only)

Add 'TR' to end of part number for Tape & Reel
Leads will be trimmed to .625" length
CK13 - 5,000 per reel
CK14 - 3,000 per reel
CK15 - 500 per reel
CK16 - 300 per reel
(Available in full reels only)

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

DISCONTINUED CONTACT KEMET FOR EQUIVALENT REPLACEMENT