



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:-20℃~70℃
 Operating force:3~20N
 Operating Life:5,000cycles

Model No.	A=φ8 L=5.7	DC-124-A	DC-124-B
	A=M8×P0.75L=5.7	DC-124M-A	DC-124M-B
	A=8 L=8.5	DC-125-A	DC-125-B
	△ A=M8×P0.75 L=8.5	DC-125M-A	DC-125M-B
Schematic			

②	Terminal	3	Phosphor bronze	Au Plating		
①	Housing	1	Nylon	Black		
ITEM	PART NAME	TERN.O.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE		TITLE: PHONE JACKES		
DRAWN J.X.Zhang		2013/11/11		ELECTRONICS CO.,LTD		
CHECKED				PART NO. DC-124		
APPROVALS				SCALE: 1:1		
TOLERANCES ARE		30~12L ±	±0.30	ANGLE	UNIT: mm	PROJ:
		10~30	±0.20			
		5~10	±0.15			
		~5	±0.10	±2'	DRAWING NO.	SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			