

- Designed to meet UL1950 and IEC 950 safety requirements
- Operating temperature range: -40° to +85° C
- Meets IEC 695, 2-2 flammability requirements
- PWB Process Capability: standard printed wiring board assembly techniques, total-immersion cleaning
- Reliability testing: shock, vibration, temperature cycling, temperature - humidity - bias
- Minimum interwinding breakdown voltage 1500 Vrms

ELECTRICAL SPECIFICATIONS AT 25° C



Part Number	Turns Ratio ±2%	DCR Ω max		Return Loss ¹ db max	Insertion Loss ² db max	Longitudinal Balance ³ db min	Harmonic Distortion ⁴ db min	Inductance ⁵ mH ±10%
	(1-3) : (2-4) : (7-5) : (8-6)	(1-4)	(8-5)					(1-4)
S560-6600-24	1 : 1 : 2 : 2	6	7	10	4	60	85	3.125

1. Measured at 100 kHz to 1 MHz
2. Measured at 1 kHz to 2 Mz
3. Measured at 20 kHz to 1 MHz
4. Measured at 3.5 Vrms, 10 kHz, Rs = 135 Ω, RL = 33.8 Ω
5. Measured at 10 kHz, connect 2 to 3

Part Number	Turns Ratio ±2%	DCR Ω max				Return Loss ¹ db max	Insertion Loss db max		Longitudinal Balance ² db min	Harmonic Distortion ³ db min
	(1-4) : (2-5) : (10-7) : (9-6)	(1-4)	(2-5)	(9-6)	(10-7)		1 kHz - 2 MHz	4 kHz - 1 MHz		
S560-6600-37	1 : 1 : 2 : 2	3	3	4	4	10	4	1.1	60	85

1. measured at 100 kHz to 200 kHz
2. measured at 20 kHz to 1 MHz
3. measured at 10 kHz


SCHEMATIC



TM00313


MECHANICAL

S560-6600-24



Dimensions are in inches [millimeters].
Standard dimension tolerance is ± 0.005 [0.13] unless otherwise noted.

S560-6600-37



©2001 Bel Fuse Inc. Specifications subject to change without notice. 06.01

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com