AUK Semiconductor

SUT488J

Epitaxial Planar Type PNP Silicon Transistor

Description

- General purpose transistor

Feature


- Two 2SA1980 chips in SOT-363 package


Ordering Information

Type NO.	Marking	Package Code
SUT488J	8X	SOT-363

Outline Dimensions

unit : mm





PIN Connections

1. Emitter 1
2. Emitter 2
3. Base 2
4. Collector 2
5. Base 1
6. Collector 1

Absolute maximum ratings (Tr1, Tr2 : PNP)

Ta=25°C

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V_{CBO}	-50	V
Collector-Emitter voltage	V_{CEO}	-50	V
Emitter-base voltage	V_{EBO}	-5	V
Collector current	I_C	-150	mA
Collector dissipation	P_C	150	mW
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55~150	°C

Electrical Characteristics (Tr1,Tr2 : PNP)

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	I_C=-100μA, I_E=0	-50	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	I_C=-1mA, I_B=0	-50	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	I_E=-10μA, I_C=0	-5	-	-	V
Collector cut-off current	I_{CBO}	V_{CB}=-50V, I_E=0	-	-	-0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=-5V, I_C=0	-	-	-0.1	μA
DC current gain	h_{FE}	V_{CE}=-6V, I_C=-2mA	120	-	400	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	I_C=-100mA, I_B=-10mA	-	-	-0.3	V
Transition frequency	f_T	V_{CE}=-10V, I_C=-1mA, f=100MHz	80	-	-	MHz
Collector output capacitance	C_{ob}	V_{CB}=-10V, I_E=0, f=1MHz	-	4	7	pF

Electrical Characteristic Curves

Tr1, Tr2 : PNP

Fig. 1 I_C -V_{BE}




Fig. 2 I_C -V_{CE}




Fig. 3 h_{FE}-I_C





Fig. 4 $V_{CE(sat)}$-I_C



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.