ASYMMETRIC DUAL N-CHANNEL ENHANCEMENT MODE MOSFET

Features


- DIOFET utilize a unique patented process to monolithically integrate a MOSFET and a Schottky in a single die to deliver:
  - Low $R_{DS(on)}$ – minimizes conduction loss
  - Low V_{SD} – reducing the losses due to body diode construction
  - Low Q_{rr} – lower Q_{rr} of the integrated Schottky reduces body diode switching losses
  - Low gate capacitance (Q_g/Q_{gs}) ratio – reduces risk of shoot-through or cross conduction currents at high frequencies
  - Avalanche rugged – I_{AR} and E_{AR} rated
- **Lead Free By Design/RoHS Compliant (Note 1)**
- **"Green" Device (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data


- Case: SO-8
- Case Material: Molded Plastic, “Green” Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram Below
- Weight: 0.072 grams (approximate)




Top View



Top View
Internal Schematic



N-Channel MOSFET +
Integrated Schottky Diode




N-Channel MOSFET

Ordering Information (Note 3)

Part Number	Case	Packaging
DMS3019SSD-13	SO-8	2500 / Tape & Reel

Notes:
1. No purposefully added lead.
2. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
3. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



© Diodes Incorporated

Maximum Ratings – Q1 @TA = 25°C unless otherwise specified

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	30	V
Gate-Source Voltage			V_{GSS}	±12	V
Continuous Drain Current (Note 4) V_{GS} = 10V	Steady State	T_A = 25°C T_A = 70°C	I_D	7.0 5.6	A
Continuous Drain Current (Note 5) V_{GS} = 10V	Steady State	T_A = 25°C T_A = 70°C	I_D	9.0 7.0	A
Continuous Drain Current (Note 5) V_{GS} = 4.5V	Steady State	T_A = 25°C T_A = 70°C	I_D	8.0 6.5	A
Pulsed Drain Current (Note 6)			I_{DM}	40	A
Avalanche Current (Notes 6 & 7)			I_{AR}	13	A
Repetitive Avalanche Energy (Notes 6 & 7) L = 0.3mH			E_{AR}	25.4	mJ

Maximum Ratings – Q2 @TA = 25°C unless otherwise specified

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	30	V
Gate-Source Voltage			V_{GSS}	±20	V
Continuous Drain Current (Note 4) V_{GS} = 10V	Steady State	T_A = 25°C T_A = 70°C	I_D	5.7 4.6	A
Continuous Drain Current (Note 5) V_{GS} = 10V	Steady State	T_A = 25°C T_A = 70°C	I_D	7.0 5.6	A
Continuous Drain Current (Note 5) V_{GS} = 4.5V	Steady State	T_A = 25°C T_A = 70°C	I_D	6.0 4.7	A
Pulsed Drain Current (Note 6)			I_D	40	A
Avalanche Current (Notes 6 & 7)			I_{AR}	16	A
Repetitive Avalanche Energy (Notes 6 & 7) L = 0.1mH			E_{AR}	12.8	mJ

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 4)	P_D	1.19	W
Thermal Resistance, Junction to Ambient @T_A = 25°C (Note 4)	$R_{\theta JA}$	107	°C/W
Power Dissipation (Note 5)	P_D	1.79	W
Thermal Resistance, Junction to Ambient @T_A = 25°C (Note 5)	$R_{\theta JA}$	70	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Notes:
4. Device mounted on FR-4 substrate PC board, with minimum recommended pad layout. The value in any given application depends on the user's specific board design. Device contains two active die running at equal power.
5. Device mounted on 1 inch x 1 inch FR4 PCB with high coverage of single sided 1oz copper, in still air conditions. Device contains two active die running at equal power.
6. Repetitive rating, pulse width limited by junction temperature.
7. I_{AR} and E_{AR} rating are based on low frequency and duty cycles to keep T_J = 25°C

© Diodes Incorporated

Electrical Characteristics – Q1 @ T_A = 25°C unless otherwise stated

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 8)						
Drain-Source Breakdown Voltage	BV_{DSS}	30	-	-	V	V_{GS} = 0V, I_D = 1mA
Zero Gate Voltage Drain Current	I_{DSS}	-	-	0.1	mA	V_{DS} = 30V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	-	-	±100	nA	V_{GS} = ±12V, V_{DS} = 0V
ON CHARACTERISTICS (Note 8)						
Gate Threshold Voltage	$V_{GS(th)}$	1.0	-	2.4	V	V_{DS} = V_{GS}, I_D = 250µA
Static Drain-Source On-Resistance	$R_{DS\ (ON)}$	-	10 12	15 18	mΩ	V_{GS} = 10V, I_D = 9A V_{GS} = 4.5V, I_D = 7A
Forward Transfer Admittance	$\|Y_{fs}\|$	-	5	-	S	V_{DS} = 5V, I_D = 9A
Diode Forward Voltage	V_{SD}	-	0.4	1	V	V_{GS} = 0V, I_S = 1A
DYNAMIC CHARACTERISTICS (Note 9)						
Input Capacitance	C_{iss}	-	1932	-	pF	V_{DS} = 15V, V_{GS} = 0V, f = 1.0MHz
Output Capacitance	C_{oss}	-	154	-		
Reverse Transfer Capacitance	C_{rss}	-	121	-		
Gate Resistance	R_g	-	2.7	-	Ω	V_{DS} = 0V, V_{GS} = 0V, f = 1MHz
Total Gate Charge (V_{GS} = 4.5V)	Q_g	-	18.1	-	nC	V_{DS} = 15V, V_{GS} = 4.5V, I_D = 9A
Total Gate Charge (V_{GS} = 10V)	Q_g	-	42.0	-		V_{DS} = 15V, V_{GS} = 10V, I_D = 9A
Gate-Source Charge	Q_{gs}	-	4.5	-		
Gate-Drain Charge	Q_{gd}	-	4.0	-		
Turn-On Delay Time	$t_{D(on)}$	-	6.16	-	ns	V_{GS} = 10V, V_{DS} = 15V, R_G = 3Ω, R_L = 1.7Ω
Turn-On Rise Time	t_r	-	7.22	-		
Turn-Off Delay Time	$t_{D(off)}$	-	36.76	-		
Turn-Off Fall Time	t_f	-	5.38	-		

Notes: 8. Short duration pulse test used to minimize self-heating effect.
9. Guaranteed by design. Not subject to production testing.




Fig. 1 Typical Output Characteristic




Fig. 2 Typical Transfer Characteristic

© Diodes Incorporated




Fig. 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 4 Typical On-Resistance vs. Drain Current and Temperature




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 On-Resistance Variation with Temperature




Fig. 7 Gate Threshold Variation vs. Ambient Temperature




Fig. 8 Diode Forward Voltage vs. Current

© Diodes Incorporated




Fig. 9 Typical Total Capacitance




Fig. 10 Typical Leakage Current vs. Drain-Source Voltage




Fig. 11 Gate-Charge Characteristics

© Diodes Incorporated

Electrical Characteristics – Q2 @ T_A = 25°C unless otherwise stated

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 8)						
Drain-Source Breakdown Voltage	BV_{DSS}	30	-	-	V	V_{GS} = 0V, I_D = 250μA
Zero Gate Voltage Drain Current	I_{DSS}	-	-	1.0	μA	V_{DS} = 30V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	-	-	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS (Note 8)						
Gate Threshold Voltage	$V_{GS(th)}$	1.0	-	2.4	V	V_{DS} = V_{GS}, I_D = 250μA
Static Drain-Source On-Resistance	$R_{DS\ (ON)}$	-	15 25	23 33	mΩ	V_{GS} = 10V, I_D = 10A V_{GS} = 4.5V, I_D = 7.5A
Forward Transfer Admittance	$\|Y_{fs}\|$	-	2.5	-	S	V_{DS} = 5V, I_D = 10A
Diode Forward Voltage	V_{SD}	-	0.65	1.0	V	V_{GS} = 0V, I_S = 1A
DYNAMIC CHARACTERISTICS (Note 9)						
Input Capacitance	C_{iss}	-	478.9	-	pF	V_{DS} = 15V, V_{GS} = 0V, f = 1.0MHz
Output Capacitance	C_{oss}	-	96.7	-		
Reverse Transfer Capacitance	C_{rss}	-	61.4	-		
Gate Resistance	R_g	0.4	1.1	1.6	Ω	V_{DS} = 0V, V_{GS} = 0V, f = 1MHz
Total Gate Charge (V_{GS} = 4.5V)	Q_g	-	5.0	-	nC	V_{DS} = 15V, V_{GS} = 4.5V, I_D = 10A
Total Gate Charge (V_{GS} = 10V)	Q_g	-	10.5	-		V_{DS} = 15V, V_{GS} = 10V, I_D = 10A
Gate-Source Charge	Q_{gs}	-	1.8	-		
Gate-Drain Charge	Q_{gd}	-	1.6	-		
Turn-On Delay Time	$t_{D(on)}$	-	2.9	-	ns	V_{GS} = 10V, V_{DS} = 15V, R_G = 3Ω, R_L = 1.5Ω
Turn-On Rise Time	t_r	-	7.9	-		
Turn-Off Delay Time	$t_{D(off)}$	-	14.6	-		
Turn-Off Fall Time	t_f	-	3.1	-		

Notes: 8. Short duration pulse test used to minimize self-heating effect.
9. Guaranteed by design. Not subject to production testing.




Fig. 12 Typical Output Characteristic




Fig. 13 Typical Transfer Characteristic

© Diodes Incorporated




Fig. 14 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 15 Typical On-Resistance vs. Drain Current and Temperature




Fig. 16 On-Resistance Variation with Temperature




Fig. 17 On-Resistance Variation with Temperature




Fig. 18 Gate Threshold Variation vs. Ambient Temperature




Fig. 19 Diode Forward Voltage vs. Current

© Diodes Incorporated




Fig. 20 Typical Total Capacitance




Fig. 21 Typical Leakage Current vs. Drain-Source Voltage




Fig. 22 Gate-Charge Characteristics





Fig. 23 Transient Thermal Response


© Diodes Incorporated

Package Outline Dimensions



SO-8		
Dim	**Min**	**Max**
A	-	1.75
A1	0.10	0.20
A2	1.30	1.50
A3	0.15	0.25
b	0.3	0.5
D	4.85	4.95
E	5.90	6.10
E1	3.85	3.95
e	1.27 Typ	
h	-	0.35
L	0.62	0.82
θ	0°	8°
All Dimensions in mm		

Suggested Pad Layout



Dimensions	Value (in mm)
X	0.60
Y	1.55
C1	5.4
C2	1.27

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2010, Diodes Incorporated

www.diodes.com