P-Channel Enhancement Mode Power MOSFET

MTP425J3


BV_{DSS}	**-30V**
I_D	**-50A**
$R_{DS(ON)}$@V_{GS}=-10V, I_D=-10A	**10mΩ(typ)**
$R_{DS(ON)}$@V_{GS}=-5V, I_D=-7A	**14mΩ(typ)**

Features

- Single Drive Requirement
- Low On-resistance
- Fast switching Characteristic
- Pb-free lead plating and halogen-free package

Symbol


MTP425J3



G：Gate
D：Drain
S：Source

Outline

TO-252(DPAK)



G D S

Ordering Information

Device	Package	Shipping
MTP425J3-0-T3-G	TO-252 (Pb-free lead plating and halogen-free package)	2500 pcs / Tape & Reel

Environment friendly grade : S for RoHS compliant products, G for RoHS compliant and green compound products

Packing spec, T3 : 2500 pcs / tape & reel, 13” reel

Product rank, zero for no rank products

Product name

Absolute Maximum Ratings (Ta=25°C)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	
Continuous Drain Current @V_{GS}=-10V, T_C=25°C		I_D	-50	A
Continuous Drain Current @V_{GS}=-10V, T_C=100°C			-32	
Continuous Drain Current @V_{GS}=-10V, T_A=25°C			-11	
Continuous Drain Current @V_{GS}=-10V, T_A=100°C			-7	
Pulsed Drain Current		I_{DM}	-100 *1	
Power Dissipation	T_C=25℃	P_D	50 *4	W
	T_C=100℃		20 *4	
	T_A=25℃		2.5	
	T_A=100℃		1.0	
Single Pulse Avalanche Energy		E_{AS}	30 *2	mJ
Single Pulse Avalanche Current		I_{AS}	-11	A
Operating Junction and Storage Temperature		Tj, Tstg	-55~+150	°C

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	$R_{th,j-c}$	2.5	°C/W
Thermal Resistance, Junction-to-ambient, max	$R_{th,j-a}$	50 *3	°C/W

Note : *1. Pulse width limited by safe operating area.

*2 . Tj=25°C, V_{DD}=-15V, L=0.5mH, R_G=25Ω.

*3 . The value of Rth,j-a is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design.

*4 . The power dissipation P_D is more useful in setting the upper dissipation limit for cases where additional heatsinking is used. It is used to determined the current rating, when this rating falls below the package limit.


Characteristics (Tj=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV_{DSS}	-30	-	-	V	V_{GS}=0V, I_D=-250μA
$V_{GS(th)}$	-1.0	-1.5	-2.5		V_{DS} = V_{GS}, I_D=-250μA
G_{FS}	-	20	-	S	V_{DS} =-5V, I_D=-10A
I_{GSS}	-	-	±100	nA	V_{GS}=±25V
I_{DSS}	-	-	-1	μA	V_{DS} =-30V, V_{GS} =0V
	-	-	-5		V_{DS} =-24V, V_{GS} =0V, Tj=55°C
*$R_{DS(ON)}$	-	9.7	13	mΩ	V_{GS} =-10V, I_D=-10A
	-	14	18		V_{GS} =-5V, I_D=-7A
Dynamic					
*Qg	-	32	-	nC	I_D=-25A, V_{DS}=-15V, V_{GS}=-10V
*Qgs	-	11.3	-		
*Qgd	-	8.4	-		

*$t_{d(ON)}$	-	17	-	ns	V_{DS}=-15V, V_{GS}=-10V, R_G=6Ω, I_D=-1A
*tr	-	10	-		
*$t_{d(OFF)}$	-	85	-		
*t_f	-	23	-		
Ciss	-	2825	-	pF	V_{GS}=0V, V_{DS}=-15V, f=1MHz
Coss	-	248	-		
Crss	-	191	-		
Source-Drain Diode					
*V_{SD}	-	-0.75	-1.2	V	I_S=-3A, V_{GS}=0V
*I_S	-	-	-50	A	
*trr	-	26	-	ns	I_S=-25A, V_{GS}=0V, dI/dt=100A/μs
*Qrr	-	18	-	nC	

*Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


Recommended soldering footprint




Unit (mm / inch)

Typical Characteristics


Typical Output Characteristics




Brekdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Tempearture




Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Tempearture




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs CaseTemperature




Typical Characteristics(Cont.)


Single Pulse Power Rating, Junction to Ambient
(Note on page 2)




Power Derating Curve




Transient Thermal Response Curves



Reel Dimension



Carrier Tape Dimension




Notes:
1. 10 sprocket hole pitch cumulative tolerance ±0.2.
2. Camber not to exceed 1mm in 100mm.
3. Material: conductive black polystyrene, antistatic coated : 10^{5} Ω/□~ 10^{11} Ω/□ unit : mm

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow




Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat −Temperature Min(Ts min) −Temperature Max(Ts max) −Time(ts min to ts max)	 100°C 150°C 60-120 seconds	 150°C 200°C 60-180 seconds
Time maintained above: −Temperature (TL) − Time (tL)	 183°C 60-150 seconds	 217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

TO-252 Dimension





3-Lead TO-252 Plastic Surface Mount Package
CYStek Package Code: J3

Style: Pin 1.Gate 2.Drain 3.Source 4.Drain

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	e	0.086	0.094	2.186	2.386
A1	0.000	0.005	0.000	0.127	e1	0.172	0.188	4.372	4.772
B	0.039	0.048	0.990	1.210	H	0.163	REF	4.140	REF
b	0.026	0.034	0.660	0.860	K	0.190	REF	4.830	REF
b1	0.026	0.034	0.660	0.860	L	0.386	0.409	9.800	10.400
C	0.018	0.023	0.460	0.580	L1	0.114	REF	2.900	REF
C1	0.018	0.023	0.460	0.580	L2	0.055	0.067	1.400	1.700
D	0.256	0.264	6.500	6.700	L3	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	P	0.026	REF	0.650	REF
E	0.236	0.244	6.000	6.200	V	0.211	REF	5.350	REF

Notes: 1.Controlling dimension: millimeters.
2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead : Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek ***semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.***
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.