


ZUP6-132/L



<b>Sales Region</b>	Worldwide
<b>Series</b>	ZUP
<b>Type</b>	800W Model
<b>Status</b>	 Production
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage[AC]	Single-phase 100V/200V
Input Voltage Range[AC]	85 to 265V
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	6V
Output Voltage[DC]	0 to 6V
Rated Output Current	132A
Output Current	0 to 132A
Rated Output Power	792W
Efficiency	77% Typ.
Voltage Ripple Noise	0.008Vrms (5Hz to 1MHz)
Current Ripple Noise	0.2Arms (5Hz to 1MHz)

### Cases Shape & Size

Case'□ shape	Bench top
Width(W)	140mm Nom.
Height(H)	153mm Nom.
Depth(D)	405.9mm Nom.
Weight	5800g Typ.

### Other

Interface Option	Front panel output jacks
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	CSA C22.2 No.1010.1-92 EN61010-1 UL3111-1
Safety Standard(Conformed)	

**Remarks** This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.