

Han Shielded power module female




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 006 3121
Specification	Han Shielded power module female
HARTING eCatalogue	https://b2b.harting.com/09140063121

Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® Shielded power module
Description of the module	With shielding plate

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	4
further contacts	+ 2 additional signal contacts + shielding
Details	Please order crimp contacts separately. 4x Han E® 2x Han D®

Technical characteristics

Conductor cross-section	[0,14] ... [4 mm²]
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated current (signal)	10 A
Rated voltage (signal)	400 V



Pushing Performance

Technical characteristics

Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	3
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	[-40] ... [+125 °C]
Mating cycles	≥ 500

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
CE	0

Commercial data

Packaging size	2
Net weight	15 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440217 Module for industrial connectors (power/signals)