



STM32-PRIMER STM3210B-PRIMER

Raisonance STM32 Primers
for fun, easy evaluation and development with STM32

Data Brief

Features

- STM32 Primer2 with STM32F103E (512 Kbytes Flash) and STM32 Primer with STM32F103B (128 Kbytes Flash):
 - In-circuit debugging/programming via dedicated USB connection to the host PC
 - Ergonomic design, MEMs-based controls tactile display, Joystick
 - Evaluation features including USB connector and MEMs sensor.
- In addition, Primer2 includes:
 - 128x160 pixel touch screen TFT display
 - Codec-based audio record and playback
 - Micro SD card
 - IrDA transceiver
 - 20-pin connector with SPI, I2C, USART, CAN and analog/digital IOs
 - Li-Ion battery with smart loading control for improved current management and extended battery life.
- In addition, Primer includes:
 - 128x128 pixel color LCD
 - buzzer and IrDA transceiver footprint.
- Ride7 development software toolset with project manager, editor and high-level language debugging (up to 32 Kbytes of code).
- GNU C/C++ compiler, no code size limitations.
- CircleOS task scheduler for dynamic loading and management of new applications.
- C source code for all sample applications and libraries including:
 - MEMs (GUI application controls)
 - TFT display (touch screen, graphical interface, games, bitmap converter)
 - Audio record and playback (Primer2)
 - And more to come.
- Dedicated online community and resources at the [stm32circle](http://stm32circle.com) web site.



Description

The STM32 Primers from Raisonance are a uniquely fun, easy, low-risk solution for exploring and developing applications for the STM32 ARM Cortex™-M3 core-based microcontrollers. When running the applications, the Primers can operate in standalone mode powered by a battery (with power management circuit on the Primer2), which is recharged via the USB connection with a host PC.

The Primers include everything that users need to better understand the STM32's peripheral implementation and operation.

Start exploring the power of the STM32 by playing with the included applications. The STM32 drives the fun, ergonomic hardware platform that combines a TFT graphical display with MEMs-based controls, (plus tactile screen and joystick with the Primer2) for navigating and controlling the GUI and game applications.

Table 1. Order codes

Part number	Order code
STM32-PRIMER	STM3210B-PRIMER
	STM3210E-PRIMER
STM3210B-PRIMER	Obsolete

Primer usage

Simply plug the Primers directly into a host PC's USB port for in-circuit debugging and device programming, then compile (no code-size limit) and debug applications (up to 32 Kbytes in Flash or RAM). For information about upgrade to the unlimited version, refer to the [stm32circle](http://stm32circle.com) web site. The Primers enable you to discover, edit and fine tune applications using Raisonance's Ride7 software toolset which drives the hardware and offers a full range of project management, source code editing and debugging features from an intuitive GUI.

You can output executables with the GNU C/C++ compiler for ARM, which has no code size limitations and is seamlessly integrated into the Ride7 interface for exceptional ease-of-use.

You can develop applications for STM32 using sample applications from Raisonance or other engineers at www.stm32circle.com as the starting point for new innovations. All the preloaded sample applications, new applications and the CircleOS task scheduler can be downloaded for free from the [stm32circle](http://stm32circle.com) web site. This Primer dedicated internet site also provides FAQ, user forums, links to development resources and much more.

Note: In addition to STM32, Raisonance Ride7 also supports the complete range of STR7/9 ARM core-based, 32-bit devices, as well as the STM8, ST7 and uPSD 8-bit microcontroller families. For details about available compilers and special features for each family, refer to the STMicroelectronics microcontroller support site on www.st.com.

Ordering information

The STM32 Primer2 and Primer are available from STMicroelectronics' sales offices and distributors. For more information and complete documentation please visit www.stm32circle.com or the STMicroelectronics microcontroller support site www.st.com or contact Raisonance.

Table 2. Order codes

Order code	Description
STM3210E-PRIMER	STM32 Primer2 with STM32F103E (512 Kbytes Flash) includes Raisonance software tools (RIDE7, GNU C/C++ compiler), CircleOS task manager and sample application code implementing a range of device peripherals. The majority of projects for the previous STM32 Primer are compatible with the STM32 Primer2.
STM3210B-PRIMER	STM32 Primer with STM32F103B (128 Kbytes Flash) includes: Raisonance software tools (Ride7, GNU C/C++ compiler), CircleOS task manager and sample application code implementing a range of device peripherals.

Revision history

Table 3. Document revision history

Date	Revision	Changes
26-Sep-2007	1	Initial release.
30-Oct-2008	2	Added the STM3210E-PRIMER details.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2008 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com