

## Han-Yellock M-c 3mm<sup>2</sup> (Au)



Image is for illustration purposes only. Please refer to product description.

Part number	11 05 000 6127
Specification	Han-Yellock M-c 3mm <sup>2</sup> (Au)
HARTING eCatalogue	<a href="https://b2b.harting.com/11050006127">https://b2b.harting.com/11050006127</a>

### Identification

Category	Contacts
Series	Han-Yellock <sup>®</sup>
Type of contact	Crimp contact

### Version

Gender	Male
Manufacturing process	Turned contacts

### Technical characteristics

Conductor cross-section	3 mm <sup>2</sup>
Conductor cross-section	AWG 12
Operating current	≤20 A
Contact resistance	≤2 mΩ
Stripping length	6.5 mm

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No



Pushing Performance

## Material properties

REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
----------------	-------------------------

## Commercial data

Packaging size	100
Net weight	0.76 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors