



Features

- Glass passivated Bridge Rectifiers
- Ideal for PCB
- High surge current capability
- Moisture sensitivity: level 1, per J-STD-020
- High temperature soldering guaranteed: 260°C/10 seconds
- Halogen-free according to IEC 61249-2-21 definition



Case Style KBF



Mechanical Data

- Case:KBF,Molding compound meets UL 94V-0 flammability rating
- Base P/N with suffix"E" on packing code-halogen free
- Terminals:Matte tin plated leads,solderable per MII-STD-750 Method 2026,J-STD-002 and JESD22-B102, meets JESD 201 class 1A whisker test

Typical Applications

General purpose use in ac-to-dc bridge full wave rectification for TV,Monitor,SMPS,Adapter, Printer,Audio equipment,and Home Applications application

Maximum Ratings (TA = 25 °C unless otherwise noted)

Parameter	Symbol	KBF401	KBF402	KBF404	KBF406	KBF408	KBF410	Unit
Maximum repetitive peak reverse voltage	VRRM	100	200	400	600	800	1000	V
Maximum RMS voltage	VRMS	70	140	280	420	560	700	V
Maximum DC blocking voltage	VDC	100	200	400	600	800	1000	V
Maximum average output rectified current	Io(AV) ¹⁾	4.0						A
	Io(AV) ²⁾	2.0						
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	150.0						A
Rating for fusing (t≤8.3ms)	I ² t	93.8						A ² s
Operating junction and storage temperature range	TJ, TSTG	-55 to 150						°C

Note1)with heatsink;

2)without heatsink

Electrical Characteristics (TA = 25 °C unless otherwise noted)

Parameter	Test Conditions	Symbol	KBF401	KBF402	KBF404	KBF406	KBF408	KBF410	Unit
Maximum instantaneous forward voltage	IF=2.0A	VF	1.0						Volts
	IF=4.0A		1.1						
Maximum DC reverse current at rated DC blocking voltage	TA=25°C	IR	5.0						μA
	TA=125°C		200.0						
Typical junction capacitance	4.0 V, 1 MHz	CJ	34.0						pF

Thermal Characteristics (Ta=25°C unless otherwise noted)

Parameter	Test Conditions	Symbol	KBF401	KBF402	KBF404	KBF406	KBF408	KBF410	Unit
Typical thermal resistance ¹⁾	junction to ambient	R _{θJA}	30						°C/W
	junction to case	R _{θJC}	8						

Note:1),The thermal resistance from junction to ambient and case,mounted on glass epoxy FR-4 P.C.B

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics





Figure 4. Typical Reverse Characteristics

Package Outline Dimensions

Unit:mm



	MIN	MAX
A	13.95	14.45
B	10.80	11.20
C	1.75 Typical	
D	13.50	14.00
E	3.61	4.01
F	1.30	1.70
G	0.90	1.10
K	2.65	2.95
L	2.00	2.20
M	0.26	0.46



KBF401 thru KBF410

Glass Passivated Single-Phase Bridge Rectifier
Reverse Voltage 100~1000V Ountput Current 4.0A

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.
(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.