TP03AC Series



DESCRIPTION: **3W 3KVAC Isolation Wide Input AC/DC Converters**

The rated output power of TP03AC series is 3W with wide input voltage range, for both AC input and DC input application. High reliability, precision, large power density, ultra-small size, no external heat sink required, stable output voltage and etc, with over current protection, EMI filter circuit, the rectifier filter circuit, 3000V isolation voltage, short circuit, overload, internal thermal protection, Widely used in telecommunications, industrial control, instrument, data acquisition, signal control and other electronic systems.

FEATURES

Universal input voltage range	Both for AC and DC input voltage	Wide input voltage:2:1 and 4:1
Fixed switching frequency	Overheat protection	Over current protection
Short circuit protection	RoHS compliant	Operating temperature :-40°C to 70°C

SELECTION GUIDE

Part Number	Input Voltage		Output		Efficiency	Recommend output external	
	Rated	Range values	Voltage（VDC)	Current	(Typ.)	C1、C2、C3	C4
	(VAC)			(A)	%		
TP03AC220S05	220(2:1)	165-265	5	0.6	71	0.1uF/25V	330uF/16V
TP03AC220S12	220(2:1)	165-265	12	0.25	76	0.1uF/25V	220uF/25V
TP03AC220S15	220(2:1)	165-265	15	0.20	77	0.1uF/25V	220uF/25V
TP03AC220S24	220(2:1)	165-265	24	0.12	77	0.1uF/25V	100uF/35V
TP03AC220D05	220(2:1)	165-265	±5	±0.3	71	0.1uF/25V	220uF/16V
TP03AC220D12	220(2:1)	165-265	±12	±0.125	76	0.1uF/25V	100uF/25V
TP03AC220D15	220(2:1)	165-265	±15	±0.1	78	0.1uF/25V	100uF/25V
TP03AC220S05W	220(4:1)	85-265	5	0.6	71	0.1uF/25V	330uF/16V
TP03AC220S12W	220(4:1)	85-265	12	0.25	76	0.1uF/25V	220uF/25V
TP03AC220S15W	220(4:1)	85-265	15	0.20	77	0.1uF/25V	220uF/25V
TP03AC220S24W	220(4:1)	85-265	24	0.12	77	0.1uF/25V	100uF/35V
TP03AC220D05W	220(4:1)	85-265	±5	±0.3	71	0.1uF/25V	220uF/16V
TP03AC220D12W	220(4:1)	85-265	±12	±0.125	76	0.1uF/25V	100uF/25V
TP03AC220D15W	220(4:1)	85-265	±15	±0.1	78	0.1uF/25V	100uF/25V
TP03AC220S06W	220(4:1)	85-265	6	0.5	71	0.1uF/25V	330uF/16V
TP03AC220S21W	220(4:1)	85-265	21	0.14	72	0.1uF/25V	100uF/35V

All specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified.

GENERAL CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation voltage	Input / Output 1 minute, leakage current 2mA		3000		VAC
Seismic	10~55Hz	5	5		G
Over current protection	Full input range		Auto recovery		
Cooling	Free air convection				
Case material	Flame-retardant plastic				

INPUT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Startup voltage	220VAC In module(165V-265V)	165	220	265	VAC
Startup voltage	220VAC In module(85V-265V)	85	220	265	VAC
Start rising time	Non-capacitive load	20			ms

Download from alldatasheet.com

OUTPUT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Voltage accuracy	Io=0.1…1.0 x Ionom Vi=Vi rated			±3	%
				±5	%
Line regulation	Vimin≤Vi≤Vimax		±0.5		%
Load regulation	Io=0.1…1.0 x Ionom Vimin≤ Vi≤Vimax		±1		%
Auxiliary voltage accuracy	Main Load and auxiliary load differ 25%,the auxiliary circuit of the load with at least 25%, the main circuit with			±3	%
Ripple and noise	20MHz bandwidth			±1	%
Over-current protection	Vimin≤Vi≤Vimax	120			%
Switch frequency	Vimin≤Vi≤Vimax		60K		Hz


ENVIRONMENT CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating temperature	industrial-class	-40		+70	℃
Maximum case temperature	industrial-class			+95	℃
Storage temperature	Industry-class	-30		+105	℃
Relative humidity	No condensation	25		90	RH(%)
Temperature coefficient			±0.02		%/℃

- Case temperature shall not exceed the maximum case temperature.

MECHANICAL DIMENSIONS

DIP Package



* Pin not fitted on single output variants

Units:mm Tolerance:±0.2mm

PIN CONNECTIONS

Pin	Single Output	Dual Output
1	N	N
2	L	L
3	+V0	+V0
4	NP	COM
5	-V0	-V0

TOPPOWER

Download from alldatasheet.com

MODEL SELECTION

TP 03 A C 220 D 05 W


- W:4:1 Wide voltage input range
- Main (auxiliary) output voltage
- S:single output, D:Dual output
- Rated input voltage
- Package type
- AC-DC
- Rated output power
- Brand name

TP 03 A C 220 T 05 D 12 W


- W:4:1 Wide voltage input range
- Auxiliary Output Voltage
- D: Auxiliary is dual output
- Main Road output voltage
- S:single output D:Dual output T:Triple output
- Rated input voltage
- Package type
- AC-DC
- Rated output power
- Brand name

RECOMMEND CIRCUIT

Single Output



Dual Output(COM)



C1, C2, C3, C4, C5, C6 capacitor values refer to parameter table

USING ATTENTIONS

- Module will cause irreversible damage when it in the long-term overload state.
- Module will cause irreversible damage when it out of the state maximum input voltage range

TOPPOWER

Download from alldatasheet.com