TSB1132

Low Frequency PNP Transistor

SOT-89

Pin assignment:
1. Base
2. Collector
3. Emitter

BV_{CEO} = - 32V
Ic = - 1A
$V_{CE\ (SAT)}$, =- 0.15V(typ.) @Ic / Ib =- 0.5A /- 50mA

Features

- Low $V_{CE\ (SAT)}$.
- Excellent DC current gain characteristics

Structure

- Epitaxial planar type.
- PNP silicon transistor

Ordering Information

Part No.	Packing	Package	Marking
TSB1132CY	Tape & Reel	SOT-89	**BK**

Absolute Maximum Rating (Ta = 25 °C unless otherwise noted)

Parameter		Symbol	Limit	Unit
Collector-Base Voltage		V_{CBO}	- 40V	V
Collector-Emitter Voltage		V_{CEO}	- 32V	V
Emitter-Base Voltage		V_{EBO}	- 5	V
Collector Current	DC	I_C	- 1	A
	Pulse		- 2.5 (note 1)	
Collector Power Dissipation	SOT-89	P_D	0.6	W
			2 (note 2)	
Operating Junction Temperature		T_J	+150	°C
Operating Junction and Storage Temperature Range		T_{STG}	- 55 to +150	°C

Note: 1. Single pulse, Pw = 10mS, Duty <= 50%
2. When mounted on a 40 x 40 x 0.7mm ceramic board

Electrical Characteristics

Ta = 25 °C unless otherwise noted

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static						
Collector-Base Voltage	I_C = - 50uA, I_E = 0	BV_{CBO}	- 40			V
Collector-Emitter Breakdown Voltage	I_C = - 1mA, I_B = 0	BV_{CEO}	- 32			V
Emitter-Base Breakdown Voltage	I_E = - 50uA, I_C = 0	BV_{EBO}	- 5			V
Collector Cutoff Current	V_{CB} = - 20V, I_E = 0	I_{CBO}			- 0.5	uA
Emitter Cutoff Current	V_{EB} = - 4V, I_C = 0	I_{EBO}			-0.5	uA
Collector-Emitter Saturation Voltage	I_C / I_B = - 500mA / - 50mA	$V_{CE(SAT)}$		- 0.15	- 0.5	V
DC Current Transfer Ratio	V_{CE} = - 3V, I_C = - 0.1A	h_{FE}	82		390	
Transition Frequency	V_{CE} = - 5V, I_C = - 50mA, f = 100MHz	f_T		150		MHz
Output Capacitance	V_{CB} = - 10V, f=1MHz	Cob		20	30	pF

Note : pulse test: pulse width <=380uS, duty cycle <=2%

Classification Of h_{FE}

Rank	P	Q	R
Range	82 - 180	120 - 270	180 - 390

Electrical Characteristics Curve

Figure 1. Current Gain vs Collector Current



Figure 2. Saturation Voltage vs Collector Current



Figure 3. Saturation Voltage vs Collector Current



Figure 4. Power Derating Curves



SOT-89 Mechanical Drawing



SOT-89 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.40	4.60	0.173	0.181
B	1.50	1.7	0.059	0.070
C	2.30	2.60	0.090	0.102
D	0.40	0.52	0.016	0.020
E	1.50	1.50	0.059	0.059
F	3.00	3.00	0.118	0.118
G	0.89	1.20	0.035	0.047
H	4.05	4.25	0.159	0.167
I	1.4	1.6	0.055	0.068
J	0.35	0.44	0.014	0.017