XC74WL08AASR

TOREX

ETR1314_001

CMOS Logic

■GENERAL DESCRIPTION

XC74WL08AASR is dual 2-input AND Gate manufactured using silicon gate CMOS processes. The small supply current, which is one of the features of the CMOS logic, gives way to high speed operations which enables LS-TTL.
With wave forming buffers connected internally, stabilized output can be achieved as the series offers high noise immunity.
As the series is integrated into a mini molded, MSOP-8B package, high density mounting is possible.

■APPLICATIONS


●Palmtops

●Digital equipment

■FEATURES

High Speed Operations : tpd = 2.6ns (TYP.) (VCC=5V)
Operating Voltage Range : 2V ~ 5.5V
Low Power Consumption: 1μA (MAX.)@Ta=25℃
CMOS Logic Dual 2-Input AND Gate
Small Package : MSOP-8B

■PIN CONFIGURATION



MSOP-8B
(TOP VIEW)

■FUNCTIONS

INPUT		OUTPUT
A	B	Y
H	H	H
H	L	L
L	H	L
L	L	L

H=High level
L=Low level

■ABSOLUTE MAXIMUM RATINGS

Ta=-40℃~85℃

PARAMETER	SYMBOL	RATINGS	UNITS
Power Supply Voltage	VCC	-0.5~+6.0	V
Input Voltage	VIN	-0.5~+6.0	V
Output Voltage	VOUT	-0.5~VCC+0.5	V
Input Diode Current	IIK	-20	mA
Output Diode Current	IOK	±20	mA
Switch Output Current	IOUT	±25	mA
VCC,GND Current	ICC,IGND	±50	mA
Power Dissipation (Ta = 25℃)	Pd	300	mW
Storage Temperature Range	Tstg	-65~+150	℃

Note : Voltage is all ground standardized.

■RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	UNITS
Supply Voltage	V_{CC}	2~5.5	V
Input Voltage	V_{IN}	0~5.5	V
Output Voltage	V_{OUT}	0~ V_{CC}	V
Operating Temperature Range	Topr	-40~+85	℃
Input Rise and Fall Time	tr,tf	0～200（V_{CC}=3.3V）	ns
		0～100（V_{CC}=5V）	

■DC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	V_{CC}(V)	CONDITIONS		Ta=25℃ MIN.	Ta=25℃ TYP.	Ta=25℃ MAX.	Ta=-40℃~85℃ MIN.	Ta=-40℃~85℃ MAX.	UNITS
Input Voltage	V_{IH}	2.0			1.5	–	–	1.5	–	V
		3.0			2.1	–	–	2.1	–	
		5.5			3.85	–	–	3.85	–	
	V_{IL}	2.0			–	–	0.5	–	0.5	V
		3.0			–	–	0.9	–	0.9	
		5.5			–	–	1.65	–	1.65	
Output Voltage	V_{OH}	2.0	V_{IN}=V_{IH}	I_{OH}=-50μA	1.9	2.0	–	1.9	–	V
		3.0			2.9	3.0	–	2.9	–	
		4.5			4.4	4.5	–	4.4	–	
		3.0		I_{OH}=-4mA	2.58	–	–	2.48	–	
		4.5		I_{OH}=-8mA	3.94	–	–	3.80	–	
	V_{OL}	2.0	V_{IN}=V_{IL} or V_{IH}	I_{OL}=50μA	–	–	0.1	–	0.1	V
		3.0			–	–	0.1	–	0.1	
		4.5			–	–	0.1	–	0.1	
		3.0		I_{OL}=4mA	–	–	0.36	–	0.44	
		4.5		I_{OL}=8mA	–	–	0.36	–	0.44	
Input Current	I_{IN}	0～5.5	V_{IN}=V_{CC} or GND		-0.1	–	0.1	-1.0	1.0	μA
Static Supply Current	I_{CC}	5.5	V_{IN}=V_{CC} or GND,I_{OUT}=0μA		–	–	1.0	–	10.0	μA

■SWITCHING ELECTRICAL CHARACTERISTICS

(tr=tf=3ns)


PARAMETER	SYMBOL	C_L	V_{CC}(V)	CONDITIONS	Ta=25℃ MIN.	Ta=25℃ TYP.	Ta=25℃ MAX.	Ta=-40℃~85℃ MIN.	Ta=-40℃~85℃ MAX.	UNITS
Delay Time	tPLH	15pF	3.3		–	3.7	8.8	1.0	10.5	ns
			5.0		–	2.8	5.9	1.0	7	
		50pF	3.3		–	5.2	12.3	1.0	14	ns
			5.0		–	3.7	7.9	1.0	9	
	tPHL	15pF	3.3		–	3.2	8.8	1.0	10.5	ns
			5.0		–	2.4	5.9	1.0	7	
		50pF	3.3		–	4.5	12.3	1.0	14	ns
			5.0		–	3.4	7.9	1.0	9	
Input Capacitance	C_{IN}	–	5.0	V_{IN}=V_{CC} or GND	–	4	10	–	10	pF
Power Dissipation Capacitance	Cpd	No Load, f=1MHz			–	9.3	–	–	–	pF

■NOISE CHARACTERISTICS


(tr=tf=3ns)

PARAMETER	SYMBOL			CONDITIONS	Ta=25℃			UNITS
		C_L	V_{CC}(V)		MIN.	TYP.	MAX.	
Non Functional Output Maximum Dynamic V_{OL}	V_{OLP}	50pF	5.0		–	0.3	0.8	V
Non Functional Output Minimum Dynamic V_{OL}	V_{OLV}	50pF	5.0		-0.8	-0.3	–	V
Minimum Dynamic V_{IH}	V_{IHD}	50pF	5.0		–	–	3.5	V
Maximum Dynamic V_{IL}	V_{ILD}	50pF	5.0		–	–	1.5	V

■TEST CIRCUIT



■WAVEFORM



PRR=1MHz
duty cycle 50%
tr=tf=3ns

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this catalog is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this catalog.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this catalog.
4. The products in this catalog are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.
   (e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this catalog within the specified ranges.
   Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this catalog may be copied or reproduced without the prior permission of Torex Semiconductor Ltd.

TOREX SEMICONDUCTOR LTD.