

















Accessories

Reflectors BR...

General data

Temperature range
Material

50 °C
acrylic

		Dimensions [mm]	Type	Reflectivity factor ¹⁾	Reflectivity surface ¹⁾	Ident. number		
Temperature range: 65 °C								
				BRT25 BRT40 BRT75 BRT84	1 1 1 1,4	0,1 0,3 1 1	37 419 37 420 37 421 30 589 79	
				BRT-42A BRT-42D	1 1	0,4 0,4	30 450 05 30 450 06	
				BRT-25R BRT-50R	1,8 1,8	0,1 0,4	30 498 09 30 498 14	
					BRT-40X18A BRT-53X19A BRT-48X32A BRT-100X18A BRT-100X55A	1,8 1,8 1,8 1,8 1,8	0,14 0,19 0,3 0,34 1	30 449 91 30 449 96 30 449 95 30 449 98 30 450 01
				BRT-40X23B BRT-48X32B BRT46	1,8 1,8 1,8	0,17 0,29 0,5	30 449 92 30 449 99 30 400 71	

¹⁾ The reflectivity factor indicates the relative reflectance per surface unit compared to the standard BRT75 reflector.

Accessories

Reflectors BR...

General data	Temperature range Material	50 °C acrylic	Dimensions [mm]	Type	Reflectivity factor ¹⁾	Reflectivity surface ²⁾	Ident number					
			BRT-60X40C BRT-77X77C BRT-92X92C	1,8	0,45	30 449 97	30 498 16	30 498 08				
BRT-60X40C	BRT-77X77C	BRT-92X92C										
Temperature range: BRL-20: 65 °C												
				BRT-40X23 BRT-48X32 BRT-100X50 BRL-20	1,8	0,17	30 449 93	30 449 94	30 450 00	37 422		
BRT-40X23	BRT-48X32	BRT-100X50	BRL-20									
Flexible reflectors			BRF50H BRF75H		0,7	1 ²⁾					37 210 00	34 124 00
Adhesive backing Length: 1 m Material: synthetic resin Temperature range: 60 °C												
Temperature range: BRT-23x14CM, BRT-32x20AM: 65 °C											BRT-23X14CM BRT-32X20AM BRT-36X40BM	1,2
BRT-23X14CM	BRT-32X20AM	BRT-36X40BM										

¹⁾ The reflectivity factor indicates the relative reflectance per surface unit compared to the standard BRT75 reflector.

²⁾ Reflectivity surface per 100 mm.