


Sales Region	USA/China/ASEAN/India
Series	PHV
Model	
Status	 Production
Option	Positive polarity
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	187 to 229VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	20000Vdc
Output Voltage Range[DC]	0 to 20000V
Rated Output Current	200mA
Output Current	0 to 200mA
Rated Output Power	4.2kW
Polarity	Positive
Power Factor	0.9
Efficiency	90% Typ.
Voltage Ripple Noise	2.05V

Package Type & Size

Package / Mounting	Rack mount
Width(W)	443mm Nom. (17.44in Nom.)
Height(H)	266mm Nom. (10.47in Nom.)
Depth(D)	650mm Nom. (25.59in Nom.)
Weight	45kg Typ. (99.2lbs Typ.)

Other

Operating Temp. Range	0 to 40°C
Storage Temp. Range	0 to 40°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	EN61010-1 CE Mark
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.